



Material Safety Data Sheet

Copyright, 2010, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) PERFECT-IT (TM) EXTRA CUT RUBBING COMPOUND PN 6060, 6061, 6058, 39018

MANUFACTURER: 3M

DIVISION: Automotive Aftermarket

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 10/19/10

Supersedes Date: 05/28/08

Document Group: 19-3261-5

Product Use:

Intended Use: Automotive

Specific Use: Removal of imperfections from painted surface.

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
WATER	7732-18-5	40 - 70
ALUMINUM OXIDE	1344-28-1	7 - 13
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	7 - 13
DECAMETHYLCYCLOPENTASILOXANE	541-02-6	< 12
DODECAMETHYLCYCLOHEXASILOXANE	540-97-6	< 8
HYDROTREATED HEAVY NAPHTHA PETROLEUM	64742-48-9	3 - 7
GLYCERIN	56-81-5	1 - 5
SOLVENT-REFINED HEAVY PARAFFINIC PETROLEUM DISTILLATES	64741-88-4	0.5 - 1.5
POLY(OXY-1,2-ETHANEDIYL)..ALPHA.-UNDECYL-.OMEGA.-HYDROXY-	34398-01-1	0.1 - 1
DISTILLATES, PETROLEUM, SOLVENT-REFINED LIGHT PARAFFINIC	64741-89-5	< 0.5
FORMALDEHYDE	50-00-0	< 0.02

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Emulsion

Odor, Color, Grade: Slight solvent odor, white emulsion

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause target organ effects. Contains a chemical or chemicals which can cause cancer.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Inhalation:

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Class Description</u>	<u>Regulation</u>
FORMALDEHYDE	50-00-0	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
FORMALDEHYDE	50-00-0	Anticipated human carcinogen	National Toxicology Program Carcinogens
FORMALDEHYDE	50-00-0	Cancer hazard	OSHA Carcinogens

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature

No Data Available

Flash Point

188 °F [*Test Method:* Closed Cup]

Flammable Limits - LEL

No Data Available

Flammable Limits - UEL

No Data Available

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

Environmental procedures

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. No smoking while handling this material. Avoid breathing of vapors, mists or spray. Avoid skin contact. Keep out of the reach of children. Avoid contact with oxidizing agents. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment. Avoid eye contact.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Use in an enclosed process area is recommended. Provide ventilation adequate to control dust concentrations below recommended exposure limits and/or control dust.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields
Indirect Vented Goggles

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges and P95 particulate prefilters . Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
ALUMINUM OXIDE	CMRG	TWA	1 fiber/cc	
ALUMINUM OXIDE	OSHA	TWA, respirable fraction	5 mg/m3	
ALUMINUM OXIDE	OSHA	TWA, as total dust	15 mg/m3	
DECAMETHYLCYCLOPENTASILOXANE	CMRG	TWA	10 ppm	
FORMALDEHYDE	ACGIH	CEIL	0.3 ppm	Sensitizer
FORMALDEHYDE	CMRG	TWA	0.5 ppm	
FORMALDEHYDE	OSHA	TWA	0.75 ppm	29 CFR 1910.1048
FORMALDEHYDE	OSHA	STEL	2 ppm	29 CFR 1910.1048
GLYCERIN	ACGIH	TWA, as mist	10 mg/m3	
GLYCERIN	OSHA	TWA, respirable fraction	5 mg/m3	
GLYCERIN	OSHA	TWA, as total dust	15 mg/m3	
HYDROTREATED HEAVY NAPHTHA PETROLEUM	3M	TWA	100 ppm	
HYDROTREATED HEAVY NAPHTHA PETROLEUM	CMRG	TWA	300 ppm	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	CMRG	TWA	300 ppm	
SOLVENT-REFINED HEAVY PARAFFINIC PETROLEUM DISTILLATES	CMRG	TWA	5 mg/m3	

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Emulsion
Odor, Color, Grade:	Slight solvent odor, white emulsion
General Physical Form:	Liquid
Autoignition temperature	<i>No Data Available</i>
Flash Point	188 °F [<i>Test Method: Closed Cup</i>]
Flammable Limits - LEL	<i>No Data Available</i>
Flammable Limits - UEL	<i>No Data Available</i>
Boiling point	212 °F
Density	1 g/ml
Vapor Density	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>

Specific Gravity	1 [Ref Std: WATER=1]
pH	8
Melting point	No Data Available
Solubility in Water	Negligible
Evaporation rate	No Data Available
Hazardous Air Pollutants	0.0191 % weight [Test Method: Calculated]
Volatile Organic Compounds	151 g/l [Test Method: calculated SCAQMD rule 443.1]
Volatile Organic Compounds	1.25 lb/gal [Test Method: calculated SCAQMD rule 443.1]
Volatile Organic Compounds	15.0 % weight [Test Method: calculated per CARB title 2]
Kow - Oct/Water partition coef	No Data Available
VOC Less H2O & Exempt Solvents	3.17 lb/gal [Test Method: calculated SCAQMD rule 443.1]
Viscosity	22000 - 28000 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

None known

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):

LB-K000-1068-0, LB-K000-1068-1, LB-K100-0349-7, 60-4100-0937-1, 60-4100-0938-9, 60-4400-9540-8, 60-4400-9967-3, 60-4550-5283-1, 60-4550-5284-9, 60-4550-5425-8, 60-9801-0936-1

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
ALUMINUM OXIDE	1344-28-1	7 - 13

STATE REGULATIONS

Contact 3M for more information.

CALIFORNIA PROPOSITION 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
FORMALDEHYDE	50-00-0	**Carcinogen

** WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 1 Flammability: 2 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

- Section 1: Product name was modified.
- Copyright was modified.
- Section 3: Potential effects from eye contact was modified.
- Section 3: Potential effects from inhalation information was modified.
- Section 5: Fire fighting procedures information was modified.
- Section 7: Handling information was modified.
- Section 7: Storage information was modified.
- Section 8: Engineering controls information was modified.
- Section 8: Eye/face protection information was modified.
- Section 8: Skin protection - recommended gloves information was modified.
- Section 8: Respiratory protection - recommended respirators information was modified.
- Section 3: Immediate other hazard(s) was modified.
- Section 14: Transportation legal text was modified.
- Page Heading: Product name was modified.
- Section 15: Inventories information was modified.
- Section 9: Density information was modified.

Section 9: Property description for optional properties was modified.
Section 14: ID Number(s) Template 1 was modified.
Section 2: Ingredient table was modified.
Section 8: Exposure guidelines ingredient information was modified.
Section 3: Carcinogenicity phrase was added.
Section 15: EPCRA 313 information was added.
Section 15: EPCRA 313 text was added.
Section 3: Carcinogenicity table was added.
Section 3: Carcinogenicity heading was added.
Section 15: California proposition 65 ingredient information was added.
Section 15: California proposition 65 heading was added.
Section 15: California proposition 65 cancer warning was added.
Section 6: Environmental procedures heading was added.
Section 6: Personal precautions heading was added.
Section 10.1 Conditions to avoid heading was added.
Section 10.2 Materials to avoid heading was added.
Section 6: Personal precautions information was added.
Section 6: Environmental procedures information was added.
Section 6: Methods for cleaning up information was added.
Section 10: Materials to avoid physical property was added.
Section 10: Conditions to avoid physical property was added.
Section 6: Clean-up methods heading was added.
Section 6: Release measures information was deleted.
Section 6: Release measures heading was deleted.
Section 10: Materials and conditions to avoid physical property was deleted.
Section 8: Exposure guidelines legend was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com

