

# SHURTAPE® HVAC PRODUCT GUIDE

**SEAL WITH  
CONFIDENCE**  
HVAC TAPES PROS TRUST

| SHURTAPE<br>PRODUCT      | TYPICAL APPLICATIONS                                                                                                                                                                                              | TAPE TYPE                                              | UL 723<br>TESTED |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|------------------|
| PC 9                     | For general purpose use in plumbing, HVAC, sealing, waterproofing and patching applications.                                                                                                                      | 9 mil Duct Tape                                        | ✓                |
| PC 609                   | For repairing thermal insulation and sealing metal ductwork; can also be used for seaming, patching and sealing in the manufactured housing industry.                                                             | 10 mil Duct Tape                                       | ✓                |
| PC 618                   | For holding, securing, seaming, repairing, bundling and splicing applications; also used as a condensation barrier in appliance assemblies.                                                                       | 10 mil Duct Tape                                       | ✓                |
| PC 621                   | For demanding HVAC applications to hold, seal and seam sheet metal and flex duct, exhaust vents and preformed insulation.                                                                                         | 11 mil Duct Tape                                       | ✓                |
| PC 622                   | For protecting window and door frames during stucco applications; can also be used for heavy duty bundling, holding and splicing jobs.                                                                            | 12.5 mil Duct Tape                                     | ✓                |
| P- 628                   | For general use in HVAC applications.                                                                                                                                                                             | 10.75 mil Gaffer's Tape                                |                  |
| PC 657®                  | For use in high performance motorsports applications, pre-manufactured housing and RV assembly, and critical industrial applications.                                                                             | 14.5 mil Duct Tape                                     | ✓                |
| PC 857<br>UL 181B-FX     | Used in the HVAC industry to seal, seam and join Class 1 Flex Duct.                                                                                                                                               | 14 mil UL 181B-FX Listed Cloth Duct Tape               | ✓                |
| DC 181<br>UL 181B-FX     | For use on Class 1 Flex Duct for connecting, joining, sealing and patching flexible air ductwork.                                                                                                                 | 2.7 mil UL 181B-FX Listed Film Tape                    | ✓                |
| SF 682                   | For airtight and moisture-free seaming, connecting, splicing, patching and sealing of sheet metal and flex duct, rigid duct boards, air vents, insulation, fibrous filter banks and pollution collection systems. | 10 mil Metalized Duct Tape                             | ✓                |
| AF 099<br>UL 181A-P/B-FX | For joining and sealing joints, connections and seams on rigid fiberglass duct board and flexible air duct.                                                                                                       | 4.1 mil UL 181A-P/B-FX Listed Aluminum Foil Tape       | ✓                |
| AF 914CT                 | For joining and sealing aluminum-backed and fibrous insulation and metal ductwork in temperatures ranging from -20 F to 260 F; can also be used to repair metal and sheet metal.                                  | 1.5 mil Dead-Soft, Cold Temperature Aluminum Foil Tape | ✓                |
| AF 975CT                 | For use in temperatures ranging from -20 F to 260 F when joining and sealing aluminum-backed or fibrous insulation and metal ductwork; can also be used to repair metal and sheet metal.                          | 2 mil Dead-Soft, Cold Temperature Aluminum Foil Tape   | ✓                |
| AF 984CT                 | For sealing seams in scrim-reinforced duct insulation when a maximum-strength tape is needed.                                                                                                                     | 7.4 mil, Cold Temperature Foil/Scrim/Kraft Tape        | ✓                |
| AF 990CT                 | For use in cold and dual temperature systems to seal, seam and join scrim-reinforced pipe and duct insulation.                                                                                                    | 8.3 mil, Cold Temperature All Service Jacket Tape      | ✓                |
| SF 685                   | For indoor or outdoor use to seal Class 1 Flex Duct, sheet metal and duct wrap vapor barriers; also approved for subgrade application on PVC-coated duct.                                                         | 17 mil Butyl Mastic Tape                               | ✓                |
| SF 686<br>UL 181B-FX     | For airtight and moisture-free sealing of Class 1 Flex Duct, sheet metal and duct wrap vapor barriers when code compliance is demanded; also approved for subgrade application on PVC-coated duct.                | 17 mil, UL 181B-FX Listed Butyl Mastic Tape            | ✓                |
| LS 300                   | For taping outdoor HVAC components.                                                                                                                                                                               | 2.85 mil, UV-Resistant Line Set Tape                   |                  |
| EV 57                    | For splicing, insulating and binding wiring harnesses.                                                                                                                                                            | UL Listed Electrical Tape                              |                  |
| EV 77                    | For primary insulation of electrical splices up to 600 V; can be used when wrapping wire harnesses and cables.                                                                                                    | UL Listed Electrical Tape                              |                  |
| VP 410                   | For general purpose floor, lane and aisle marking; also used for wrapping line sets.                                                                                                                              | Line Set Tape                                          |                  |

# SHURTAPE® HVAC CROSS REFERENCE

**SEAL WITH  
CONFIDENCE**  
HVAC TAPES PROS TRUST

| SHURTAPE                 | POLYKEN/<br>NASHUA                 | 3M/<br>VENTURE | FASSON         | IDEAL             | IPG/<br>Hardcast                       |
|--------------------------|------------------------------------|----------------|----------------|-------------------|----------------------------------------|
| PC 9                     | 203/2280                           | 1500           |                |                   | AC 30                                  |
| PC 609                   | 243/396/398                        | 1500           |                |                   | AC 30                                  |
| PC 618                   | 213/223                            | 6969           | 950            |                   | AC 30                                  |
| PC 621                   | 229/236                            |                |                |                   | AC 36                                  |
| PC 622                   | 253/345/354                        | 1557           |                |                   | AC 45                                  |
| P- 628                   | 510/512                            | 6910           |                |                   |                                        |
| PC 857<br>UL 181B-FX     | 557 UL 181B-FX<br>558CA UL 181B-FX |                | 957            | FLEX SEAL™<br>457 | AC 57                                  |
| DC 181<br>UL 181B-FX     | 555 FlexFix<br>UL 181B0FX          | 1599B          | FAS-FLEX       | FLEX SEAL™<br>450 | AC 698                                 |
| SF 682                   | 251/365                            | 1502           |                | 468               | AC 49                                  |
| AF 099<br>UL 181A-P/B-FX | 324A/339                           | 1581A          | 0810/0800      | IS 2000<br>587A/B | ALF-201L                               |
| AF 914CT                 | 332                                | 3531/1520CWT   | 1803/0812      | 488S              | ALF-150L                               |
| AF 975CT                 | 322/330/330X                       | 3530/3520CW    | 0802/0808/0817 | 488/788           | ALF-200L                               |
| AF 984CT                 | FSK/338/438                        | 1525CWT        | 0821/0827/0828 | 491/791           | FSK-1                                  |
| AF 990CT                 | ASJ/348                            | 1540CW         | 0838           | 428               | ASJ-1                                  |
| SF 685                   | 327/360-17                         |                |                |                   | Hardcast 1402                          |
| SF 686<br>UL 181B-FX     | 367-17<br>UL 181B-FX               | 1580           |                |                   | Hardcast<br>1404/1403<br>1404 181 B-FX |
| LS 300                   | 444                                | 1507           |                |                   |                                        |
| EV 57                    | B17                                | TEMFLEX 1700   |                |                   |                                        |
| EV 77                    |                                    | 33+/35         |                |                   |                                        |
| VP 410                   |                                    | 471            |                |                   |                                        |

SHURTAPE.COM  
1.888.442.TAPE



**Shurtape®**  
**TRUE TO YOUR WORK®**

**FOR REFERENCE ONLY**

© Shurtape Technologies, LLC 2025/MMC 01468