


Permanent Split Capacitor, Direct Drive Fan & Blower, 5.6" Diameter, Open Air Over




APPLICATIONS:

Designed to meet manufacturer's requirements for use on direct drive fans and blowers.

FEATURES:

- Stud Extensions on Popular Models
- Designed for use with 370V Capacitors
- Class B Insulation
- Continuous Duty, Air Over
- Bearings Have All Angle Thrust System
- Reversible Rotation
- For Belly Band Mounts, see HVAC Motor Accessories page
- Automatic Reset Thermal Overload Protector
- Connection & Capacitor Information Furnished in Nameplate Data
- All Angle Mount
- 2.5" Dia. Hub Rings Included



Multi-Horsepower

HP	RPM/Spds.	Voltage	Catalog Number	List	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Ship Wt. (lbs)	Notes
1/2 - 1/6	1075 / 4 SPD	115	3314	\$171	10	7.3-2.8	5.0	5.9	5.3	10.8	13.5	H40
	1075 / 4 SPD	208-230	3315	\$176	10	3.6	5.0	5.9	5.3	12.2	13.5	H40
3/4 - 1/5	1075 / 4 SPD	115	3312	\$208	20	8.1-3.1	5.0	6.6	6.1	12.2	16.6	H40
	1075 / 4 SPD	208-230	3313	\$216	20	3.8	5.0	6.6	6.1	12.2	16.6	H40

Two Speed

HP	RPM/Spds.	Voltage	Catalog Number	List	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Ship Wt. (lbs)	Notes
1/4	1075 / 2 SPD	115	3197	\$166	5	3.9	5.0	5.4	4.9	10.4	12.1	-
1/3	1075 / 2 SPD	460	8945	\$638	5	1.3	6.0	5.3	4.8	11.9	18.1	64
1/2	825 / 2 SPD	208-230	3183	\$438	10	3.9	4.0	6.1	5.6	10.7	20.9	64,TR
3/4	1075 / 2 SPD	460	8947	\$681	20	2.2	6.0	6.1	5.6	12.6	18.1	64

Three Speed

HP	RPM/Spds.	Voltage	Catalog Number	List	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Ship Wt. (lbs)	Notes
1/4	1625 / 3 SPD	115	1690	\$289	10	2.7	6.0	4.6	4.1	11.1	12.79	-
	1075 / 3 SPD	115	1863	\$152	7.5	3.5	5.0	5.4	4.9	10.4	11.01	-
	1075 / 3 SPD	208-230	1971	\$154	7.5	1.5	5.0	4.9	4.4	10.4	10	-
	1075 / 3 SPD	277	600	\$319	4	2.0	5.0	5.2	4.6	11.7	7.92	69
1/3	1625 / 3 SPD	115	1692	\$297	15	3.7	6.0	4.8	4.3	11.4	11.4	-
	1625 / 3 SPD	208-230	1693	\$227	5	2.1-1.4	4.5	5.1	4.6	10.7	15.2	-
	1075 / 3 SPD	115	1864	\$156	7.5	5.0	5.0	5.6	5.1	10.7	12	-
	1075 / 3 SPD	208-230	1972	\$160	7.5	1.9	5.0	5.6	5.1	10.7	10.86	-
	1075 / 3 SPD	277	601	\$295	4	2.2	6.0	5.5	5	11.9	16.16	69
1/2	1625 / 3 SPD	115	1694	\$318	20	5.5	5.0	5.9	5.3	11.4	15.59	-
	1625 / 3 SPD	208-230	1695	\$324	7.5	3.1-3.0	5.0	5.9	5.3	11.4	22.6	-


Note 64 - Capacitor Supplied Detached

Note 69 - No Stud Extension

Note H40 - Screws For Shell Mounting Included In Carton

Note TR - OEM to Trane

Permanent Split Capacitor, Direct Drive Fan & Blower, 5.6" Diameter, Open Air Over



Three Speed

HP	RPM/Spds.	Voltage	Catalog Number	List	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Ship Wt. (lbs)	Notes
1/2	1075 / 3 SPD	115	1865	\$188	10	6.5	5.0	5.9	5.4	11.4	15	-
	1075 / 3 SPD	115	1323	\$189	15	5.0	3.5	-	4.8	8.3	11.67	H40,RH
	1075 / 3 SPD	208-230	1973	\$195	10	2.9	5.0	6.2	5.7	11.7	17	-
	1075 / 3 SPD	277	602	\$404	6	3.4	6.0	5.7	5.2	12.1	17.31	69
3/4	1625 / 3 SPD	115	1696	\$338	15	8.6	6.0	5.9	5.4	12.4	19.2255	-
	1625 / 3 SPD	208-230	1697	\$345	10	4.4-4.2	6.0	5.9	5.4	12.4	17.96	-
	1075 / 3 SPD	115	8904	\$215	15	9.5	5.0	6.4	5.9	11.4	16	-
	1075 / 3 SPD	208-230	8905	\$216	15	4.0	5.0	6.6	6.1	11.6	18	-
	1075 / 3 SPD	277	5847	\$403	15	4.1	6.0	6.7	6.2	13.2	19.78	69
1	1625 / 3 SPD	115	1699	\$358	25	11.1	6.0	6.4	5.9	12.9	21.9555	-
	1625 / 3 SPD	208-230	1700	\$376	20	5.1	6.0	5.8	5.3	12.4	19.7	-
	1100 / 3 SPD	460	2553	\$542	25	3.3	3.5	-	6.8	10.3	21.82	H11,YK
	1075 / 3 SPD	115	8906	\$298	20	12.1	5.0	6.6	6.1	12.2	21.86	-
	1075 / 3 SPD	208-230	8907	\$301	20	5.6	5.0	6.6	6.1	12.2	21.86	-

Stud or Hub Ring Mount, Four Speed

HP	RPM/Spds.	Voltage	Catalog Number	List	Cap. MFD	Amps	Shaft N	Base XD	Shell XI	Total C	Ship Wt. (lbs)	Notes
1/6	1075 / 4 SPD	115	5825	\$189	4	2.2	6.0	4.6	4.1	11.1	12	-
	1075 / 4 SPD	208-230	5826	\$191	5	1.1	6.0	4.6	4.1	11.1	9.912	-
1/4	1075 / 4 SPD	115	5830	\$191	5	3.8	6.0	4.9	4.4	11.4	15.2	-
	1075 / 4 SPD	208-230	5831	\$196	5	1.8-1.7	6.0	4.9	4.4	11.4	12.642	-
1/3	1075 / 4 SPD	115	5835	\$215	7.5	4.6	6.0	5.4	4.9	11.9	19.6	-
	1075 / 4 SPD	208-230	5836	\$216	6	2.3-2.2	6.0	5.1	4.6	11.6	13.06	-
1/2	1075 / 4 SPD	115	5840	\$231	7.5	7.1	6.0	5.8	5.3	12.4	19.68	-
	1075 / 4 SPD	208-230	5841	\$248	7.5	3.3-3.1	5.8	5.6	5.1	12.7	20.4	-
3/4	900 / 4 SPD	115	1125	\$391	10	11.9	4.0	-	6.6	10.6	24.1	H11,H16,IC
	1075 / 4 SPD	115	5845	\$307	15	10.6	6.0	6.1	5.6	12.6	22.4	-
	1075 / 4 SPD	115	6452	\$299	15	11.2	5.0	-	5.8	10.8	22.12	69,H11,H16
	1075 / 4 SPD	115	5463	\$368	15	10.6	5.0	-	5.8	10.8	20.1	H40,RH
	1075 / 4 SPD	208-230	5846	\$323	10	6.1-5.8	6.0	6.1	5.6	12.6	23	-

Note 69 - No Stud Extension

Note H11 - Band Mount

Note H16 - CCWLE rotation only

Note H40 - Screws For Shell Mounting Included In Carton

Note IC - OEM to ICP

Note RH - OEM to Rheem

Note YK - OEM to York