



Beautiful Made Easy




Fusion + Waves

3.0 mm Luxury Vinyl Plank


UNIQUE FEATURES




Stain & Scratch
Resistant



Light Commercial
Foot Traffic



Easy
Installation



Zero
Maintenance




Natural Looking
Design




Easy Clean

INSTALLATION PATTERN


Herringbone




Double Herringbone




Basket Wave




Diagonal Basket Wave



Diagonal Herringbone



Brick



"Wide Planks. Seamless Sophistication. Fusion features longer and wider planks that create a sense of openness and continuity across larger spaces. Perfect for residential - living rooms, bedrooms etc & semi-commercial areas - lobby areas, restaurants etc, it delivers a spacious, modern aesthetic with natural wood-inspired textures."



"Crafted with European design precision, Fusion offers durability, water and scratch resistance, and low maintenance for everyday living. Its soft touch surface provides warmth and comfort, while the easy glue down installation ensures a quick, clean, and professional finish."

Fusion





SNOW PINE | F1003
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



SILVER DRIFTWOOD | F1004
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



URBAN TIMBER | F1007
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



HARVEST PINE | F1009
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



HONEY OAK | F1011
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



AUTUMN TEAK | F1012
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



GOLDEN OAK | F1014
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



SLATE ASH | F1016
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



DARK MAHOGANY | F1018
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



GOLDEN ACACIA | F1021
Thickness - 3.0 mm

Plank Size - 7.2" x 48"
10 Pcs per box / 24 Sqft



Waves



"Herringbone Elegance. European Charm. Waves is a 3mm Luxury Vinyl Plank collection designed in the timeless Herringbone pattern, bringing refined rhythm and visual depth to interiors. Ideal for residential - living rooms, bedrooms etc & semi-commercial areas - lobby areas, restaurants etc, it adds a touch of European sophistication to contemporary spaces. With authentic wood grain textures and elegant finishes."



" Waves combines classic craftsmanship with modern performance. Durable, water-resistant, and easy to maintain, it ensures lasting beauty and comfort underfoot, with a seamless glue down installation for a perfect fit every time."



RUSTIC ALMOND | WA - 1140
Thickness - 3.0 mm

Plank Size - 4" x 18"
48 Pcs per box / 24 Sqft



BERRY CRIMSON | WA - 1190
48 Pcs per box / 24 Sqft

Plank Size - 4" x 18"
48 Pcs per box / 24 Sqft



GRAPHITE GLAM I WA - 2060
48 Pcs per box / 24 Sqft

Plank Size - 4" x 18"
48 Pcs per box / 24 Sqft



LUNAR DRIFT | WA - 3110
48 Pcs per box / 24 Sqft

Plank Size - 4" x 18"
48 Pcs per box / 24 Sqft



SILVER WHISPER | WA - 3020
48 Pcs per box / 24 Sqft

Plank Size - 4" x 18"
48 Pcs per box / 24 Sqft



SMOKE VEIL | WA - 3130
48 Pcs per box / 24 Sqft

Plank Size - 4" x 18"
48 Pcs per box / 24 Sqft



CHOCO LAVA | WA - 2110
48 Pcs per box / 24 Sqft

Plank Size - 4" x 18"
48 Pcs per box / 24 Sqft



NUDE NOUVEAU | WA - 1100
48 Pcs per box / 24 Sqft

Plank Size - 4" x 18"
48 Pcs per box / 24 Sqft

STANDARD INSTALLATION GUIDELINE				
1. Site & Subfloor Preparation				
• Ensure the subfloor (cement, tiles, marble, or plywood) is dry, level, and clean.				
• New cement floors must be fully cured (minimum 45 days) before installation.				
• Remove dust, oil, paint, or loose material from the floor.				
• Subfloor unevenness should not exceed 3 mm over 2 meters. Use self-levelling compound if needed.				
2. Acclimatization of Planks				
• Keep the LVP boxes flat in the room (not standing vertically).				
• Let the planks rest for 48 hours at room temperature (20–35°C) before installation.				
• Do not install in areas exposed to direct sunlight.				
3. Installation Method				
• Must use a water-based adhesive suitable for Indian humidity.				
4. After Installation – Care & Maintenance				
• Do not use harsh acid/ phenyl-based cleaners (common in India). Use pH-neutral floor cleaners.				
• Clean with dry mop or damp cloth only.				
• Wipe spills immediately – though LVP is water-resistant, standing water can seep into joints.				
• Use felt pads under furniture legs.				
• For rolling chairs, use a protective mat.				

DESCRIPTION				
Total Thickness	EN428	mm	3.0mm	
Thickness of Wear layer	EN429	mm	0.3	
Weight	EN430	g/m²	2741	2741
Plank Size	EN427	inch	7.2x48	4x18
Number of floor per package	-	-	10 PCS	48 PCS
CLASSIFICATION				
Norm/Product specification	-	-	EN 649	
European classification	EN 685	class	34-43	
Fire rating	EN 13 501-1	class	Bf-1	
Static electrical propensity	EN 1815	kv	< 2.0	
Slip resistance wet: ramp test with oil	DIN 51 130	class	R10	
PERFORMANCE				
Wear resistance	EN 660.2	mm³	≤2.0	
Wear group	EN 649	-	T	
Dimensional stability	EN 434	%	≤0.15	
Residual indentation	EN 433	mm	0.10	
Thermal conductivity	EN 12524	W/(m.K)	0.21	
Sound Reduction	DIN 52210	db	4.00	
Color fastness	EN 20 105-B02	degree	≥6	
Chemical products resistance	EN 423	-	Pass	
Surface treatment	-	-	UV	



Beautiful ✦ Made Easy



www.excelwallpapers.com