

RADIANT HEAT | A COMFORTABLE ENVIRONMENT NO MATTER THE WEATHER OUTSIDE

MEET THE **SunStar** GLASS

The SunStar *GLASS* infrared gas heater is a two-stage heater, with featured tinted *high-temperature glass*, which provides protection on windy days and enhances the aesthetic appeal of any design.



FEATURED MODEL: MGL - 316 MARINE GRADE STAINLESS



FEATURED MODEL: SGL - 3MIL BLACK POWDER COAT



SGL



MGL



WIND RESISTANT UP TO 40MPH



RAIN + SNOW RESISTANT




35,000 OR 50,000 BTU MODELS AVAILABLE



24,000-35,000 OR 34,000 -50,000 BTU



UP TO 60-DEG. HORIZONTAL MOUNTING






REDUCED CLEARANCES UP TO 10" *



WIRELESS REMOTE OPERATION *





CSA DESIGN CERTIFIED - Z83.19 & Z83.26





MODEL	GAS TYPE	BTUS 2-STAGE	MOUNTING HEIGHT	HEATER SPACING	MOUNTING ANGLE	HEATER DIMENSIONS	2-STAGE SWITCH INCLUDED	WIRELESS REMOTE OPERATION*	TIMER CONTROL	HEAT-SHIELD INCLUDED*
N7SGL0	NATURAL	24,000 LOW 35,000 HIGH	8-11 FT.	8-16 FT.	O-DEG.	48" X 11.5" X 9.5"	YES	NO	OPTIONAL	YES
L7SGL0	PROPANE	24,000 LOW 35,000 HIGH	8-11 FT.	8-16 FT.	O-DEG.	48" X 11.5" X 9.5"	YES	NO	OPTIONAL	YES
N10SGL0	NATURAL	24,000 LOW 35,000 HIGH	8-11 FT.	8-16 FT.	O-DEG.	48" X 11.5" X 9.5"	YES	YES	OPTIONAL	YES
L10SGL0	PROPANE	24,000 LOW 35,000 HIGH	8-11 FT.	8-16 FT.	O-DEG.	48" X 11.5" X 9.5"	YES	YES	OPTIONAL	YES
N7MGL0	NATURAL	24,000 LOW 35,000 HIGH	8-11 FT.	8-16 FT.	O-DEG.	48" X 11.5" X 9.5"	YES	NO	OPTIONAL	YES
L7MGL0	PROPANE	24,000 LOW 35,000 HIGH	8-11 FT.	8-16 FT.	O-DEG.	48" X 11.5" X 9.5"	YES	NO	OPTIONAL	YES
N10MGL0	NATURAL	24,000 LOW 35,000 HIGH	8-11 FT.	8-16 FT.	O-DEG.	48" X 11.5" X 9.5"	YES	YES	OPTIONAL	YES
L10MGL0	PROPANE	24,000 LOW 35,000 HIGH	8-11 FT.	8-16 FT.	O-DEG.	48" X 11.5" X 9.5"	YES	YES	OPTIONAL	YES
N7SGL1560	NATURAL	24,000 LOW 35,000 HIGH	7-9 FT.	6-14 FT.	15-60 DEG.	48" X 11.5" X 9.5"	YES	NO	OPTIONAL	NO
L7SGL1560	PROPANE	24,000 LOW 35,000 HIGH	7-9 FT.	6-14 FT.	15-60 DEG.	48" X 11.5" X 9.5"	YES	NO	OPTIONAL	NO
N10SGL1560	NATURAL	24,000 LOW 35,000 HIGH	7-9 FT.	6-14 FT.	15-60 DEG.	48" X 11.5" X 9.5"	YES	YES	OPTIONAL	NO
L10SGL1560	PROPANE	24,000 LOW 35,000 HIGH	7-9 FT.	6-14 FT.	15-60 DEG.	48" X 11.5" X 9.5"	YES	YES	OPTIONAL	NO
N7MGL1560	NATURAL	24,000 LOW 35,000 HIGH	7-9 FT.	6-14 FT.	15-60 DEG.	48" X 11.5" X 9.5"	YES	NO	OPTIONAL	NO
L7MGL1560	PROPANE	24,000 LOW 35,000 HIGH	7-9 FT.	6-14 FT.	15-60 DEG.	48" X 11.5" X 9.5"	YES	NO	OPTIONAL	NO
N10MGL1560	NATURAL	24,000 LOW 35,000 HIGH	7-9 FT.	6-14 FT.	15-60 DEG.	48" X 11.5" X 9.5"	YES	YES	OPTIONAL	NO
L10MGL1560	PROPANE	24,000 LOW 35,000 HIGH	7-9 FT.	6-14 FT.	15-60 DEG.	48" X 11.5" X 9.5"	YES	YES	OPTIONAL	NO
50N7SGL0	NATURAL	34,000 LOW 50,000 HIGH	9-12 FT.	8-11 FT.	O-DEG.	48" X 13" X 9.5"	YES	NO	OPTIONAL	YES
50L7SGL0	PROPANE	34,000 LOW 50,000 HIGH	9-12 FT.	8-11 FT.	O-DEG.	48" X 13" X 9.5"	YES	NO	OPTIONAL	YES
50N10SGL0	NATURAL	34,000 LOW 50,000 HIGH	9-12 FT.	8-11 FT.	O-DEG.	48" X 13" X 9.5"	YES	YES	OPTIONAL	YES
50L10SGL0	PROPANE	34,000 LOW 50,000 HIGH	9-12 FT.	8-11 FT.	O-DEG.	48" X 13" X 9.5"	YES	YES	OPTIONAL	YES
50N7SGL1560	NATURAL	34,000 LOW 50,000 HIGH	9-12 FT.	8-11 FT.	15-60 DEG.	48" X 13" X 9.5"	YES	NO	OPTIONAL	NO
50L7SGL1560	PROPANE	34,000 LOW 50,000 HIGH	9-12 FT.	8-11 FT.	15-60 DEG.	48" X 13" X 9.5"	YES	NO	OPTIONAL	NO
50N10SGL1560	NATURAL	34,000 LOW 50,000 HIGH	9-12 FT.	8-11 FT.	15-60 DEG.	48" X 13" X 9.5"	YES	YES	OPTIONAL	NO
50L10SGL1560	PROPANE	34,000 LOW 50,000 HIGH	9-12 FT.	8-11 FT.	15-60 DEG.	48" X 13" X 9.5"	YES	YES	OPTIONAL	NO



MANUFACTURED BY:



* WIRELESS REMOTE OPERATION INCLUDED ON N10 & L10 MODELS ONLY
* HEAT-SHIELD REQUIRED TO MEET MINIMUM CLEARANCE OF 10"

DISTRIBUTED BY:



DEFINING THE OUTDOOR GRILLING
& COMFORT HEAT EXPERIENCE SINCE 1966
AEICORPORATION.COM 949-474-3070

