

PowerSpin™ HX Centrifuge

Product Images



Short Description

POWERSPIN™ HX CENTRIFUGE
FIXED SPEED 3400 RPM
6 PLACE HORIZONTAL ROTOR
30 MIN. DIGITAL TIMER
6 X10ML CAPACITY
POWER INPUT 110V

Description

UNICO PowerSpin™ HXV Series benchtop centrifuges are economical, reliable and super quiet available with horizontal or 12 place fixed angle rotors.

The horizontal rotor insures clean, complete separation of cellular components yielding a superior serum or plasma specimen. Using a horizontal rotor for spinning Serum Separator Tubes (SSTs) creates a tight uniform horizontal seal, reducing the risk of red cell leakage and possibility of specimen deterioration. This is especially important when the specimen is sent out for testing.

The PowerSpin™ HXV features electronically controlled safety lock, so the lid can not be opened while the rotor is in motion. A digital timer and LCD display provide user with the precise control of the spin cycle. Powerful brushless motor is maintenance free for years of dependable use. Stainless steel guard bowl is easy to clean and maintain.

The PowerSpin™ HXV features a Zero RPM safety lock, so the lid cannot be opened while the rotor is in motion. A digital timer and LCD display provide user with the precise control of the spin cycle.

Powerful 100W brushless motor is maintenance free for years of dependable use. Stainless steel guard bowl adds even more protection, and also is easy to clean and maintain.

Additional Information

	Header	Accessories
	C8300-01	6 place horizontal rotor for HXV C8300 centrifuge
	C8300-02	8 place horizontal rotor for HXV C8300 centrifuge
	C8300-03	12 place angled rotor for HXV C8300 centrifuge
Accessories	C800-02	Regular tube shield, pack of 2
	C800-03	Adapter for short tubes, pack of 10
	C800-04	Pediatric or microtube adapter, pack of 2
	C800-05	Tube Lift Adapters, Pk/12
	C800-12	Balance Tube Holdster

Specification

Speed (RPM)	3500
Maximum RCF (g)	1777g
Timer	Digital
Nominal Capacity	6 x 15 ml
Rotor	Horizontal
Lock	ZERO RPM Digital
Motor	AC
Maximum Test Tube Size	16 x 110 mm