

Eastman Tritan[™] copolyester— What about microwave applications?

Eastman Chemical Company has conducted extensive evaluation of Eastman Tritan[™] copolyester for food contact applications and obtained clearance from the United States Food and Drug Administration (FDA) for use of Tritan copolyesters in repeated use food contact articles on the basis of 21 CFR 174.5(d)(5) as a component in the manufacture of repeated use food contact articles as described in FCN No. 1041 (http://www.accessdata.fda.gov/scripts/fcn/ fcnDetailNavigation. cfm?rpt=fcslisting&id=1041). Under FCN No. 1041, Eastman Tritan copolyester is cleared for uses in food contact at temperatures up to and including 100°C (212°F), temperatures that can be achieved through conventional, convection, or microwave heating. (For definitions of food types, refer to Tables 1 and 2 at http://www.fda.gov/ Food/FoodIngredientsPackaging/FoodContactSubstancesFCS/ ucm109358.htm). The use of Tritan is also subject to the limitations stated in 21 CFR 174.5.

Eastman Tritan™ copolyester has been cleared for food contact applications; however, the suitability of any polymer for heating or reheating food can be influenced by the design of the article and food type and should be evaluated on a case-by-case basis. The use of any food contact substance to fabricate food contact articles is done with the understanding that it is the responsibility of the manufacturer of the end-use article to ensure that any resultant food contact articles comply with the specifications and limitations in all applicable regulations. Any article used in a food contact application must be suitable for the intended use under the FDA's good manufacturing practices regulation at 21 CFR 174.5 ("General provisions applicable to indirect food additives").

Eastman and its marketing affiliates shall not be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of suitability for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product, and nothing herein waives any of the seller's conditions of sale.



EASTMAN

Eastman Chemical Company Corporate Headquarters

P.O. Box 431 Kingsport, TN 37662-5280 U.S.A.

Telephone: U.S.A. and Canada, 800-EASTMAN (800-327-8626) Other Locations, (1) 423-229-2000 Fax: (1) 423-229-1193

Eastman Chemical Latin America

9155 South Dadeland Blvd. Suite 1116 Miami, FL 33156 U.S.A.

Telephone: (1) 305-671-2800 Fax: (1) 305-671-2805

Eastman Chemical B.V.

Fascinatio Boulevard 602-614 2909 VA Capelle aan den IJssel The Netherlands

Telephone: (31) 10 2402 111 Fax: (31) 10 2402 100

Eastman (Shanghai) Chemical Commercial Company, Ltd. Jingan Branch

1206, CITIC Square No. 1168 Nanjing Road (W) Shanghai 200041, P.R. China

Telephone: (86) 21 6120-8700 Fax: (86) 21 5213-5255

Eastman Chemical Japan Ltd.

MetLife Aoyama Building 5F 2-11-16 Minami Aoyama Minato-ku, Tokyo 107-0062 Japan

Telephone: (81) 3-3475-9510 Fax: (81) 3-3475-9515

Eastman Chemical Asia Pacific Pte. Ltd.

#05-04 Winsland House 3 Killiney Road Singapore 239519

Telephone: (65) 6831-3100 Fax: (65) 6732-4930

www.eastman.com

The results of **insight**™

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company makes no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of their suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Material Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2013 Eastman Chemical Company. Eastman, The results of insight, and Tritan are trademarks of Eastman Chemical Company.