

IP4M-1026E

Amcrest 4MP ProHD POE Outdoor Network Bullet Camera

Technical Specifications

Model	IP4M-1026EW / IP4M-1026EB
Camera	
Image Sensor	1/3" 4 Megapixel progressive scan CMOS
Effective Pixels	2688*1520
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3s~1/100000s
Minimum Illumination	0.53Lux/F2.0 (Color); 0Lux/F2.0 (IR on)
S/N Ratio	45DB
IR Distance	Up to 30m (98.2ft)
Video	
Compression	H.265/H.264H
Streaming Capability	2 Streams
Resolution	4MP(2688x1520)@30fps, 3MP(2304x1296)@30fps 1080P(1920x1080)@30fps, 720P(1280x720)@30fps, VGA@30fps
Frame Rate	Main Stream: 4MP/3MP/1080P/720P @ 30fps Substream: VGA
Bit Rate	H.264H: 24K ~ 10240Kbps, H.265 : 14K ~ 6912Kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC /HLC /DWDR
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
Max. User Access	20 users
Edge Storage	NAS, FTP, Local PC

Management Software	Amcrest Surveillance Pro (Windows/MAC) Amcrest View Pro app for IOS and Android AmcrestCloud.com Video Storage Subscription Service (Chrome, Edge, Firefox, Safari) Blue Iris Professional (Third Party) Web Browser (Pale Moon, Sea Monkey, Firefox 49.0, Internet Explorer, Chrome with Amcrest Extension, Safari)
Camera Features	
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Digital Zoom	16x
Motion Detection	Off/On (4 Zone, Rectangle)
Smart IR	Auto/Manual
Flip	0°/90°/180°/270°
Mirror	Off/On
Privacy Masking	Up to 4 areas
Lens	
Lens Type	Fixed
Mount Type	Board-in
Focal Length	2.8mm
Max. Aperture	F2.0
Angle of View	118°(Diagonal)
Focus Control	Manual
General	
Power Supply	DC12V, 2.0A, PoE (IEEE 802.3af)(Class 0)
Power Consumption	<6W(POE)
Operating Conditions	-10 °C~+50 °C,(14°F~122°F) Less than 95% RH
Ingress Protection	IP67
Storage Conditions	-10 °C~+50 °C,(14°F~122°F) Less than 95% RH
Casing	Metal
Dimensions	6.6" x 3.25" x 2.75"
Weight	0.45kg (1lbs)