

IP4M-1026E

4MP ProHD POE Outdoor Network Bullet Camera

Technical Specifications

Model	IP4M-1026E
Camera	
Image Sensor	1/3" 4 Megapixel progressive scan CMOS
Effective Pixels	2688*1520
RAM/ROM	512MB/32MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3s~1/100000s
Minimum Illumination	0.53Lux/F2.0 (Color); 0Lux/F2.0 (IR on)
S/N Ratio	45dB
IR Distance	Distance up to 30m
Video	
Compression	H.265/H.264H//H.264

Resolution	4MP(2688x1520)@30fps 3MP(2304x1296)@30fps 1080P(1920x1080)@30fps 720P(1280x720)@30fps VGA@30fps
Frame Rate	Main Stream: 4MP/3MP/1080P/720P@30fps
	Sub Stream: VGA

Bit Rate Control	CBR/VBR
Bit Rate	H.264H: 24K ~ 10240Kbps H.265: 14K ~ 6912Kbps
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4/IPv6,HTTP,HTTPS,SSL,TCP/IP, UDP,UPnP, ICMP,IGMP,SNMP,RTSP,RTP, SMTP, NTP,DHCP, DNS,PPPOE,DDNS,FTP, IP Filter,QoS,Bonjour,802.1x
Interoperability	ONVIF, PSIA, CGI
Streaming Method	Unicast / Multicast
Max. User Access	20 users
Edge Storage	NAS (Network Attached Storage),Local PC for instant recording, Micro SD card 256GB

Web Viewer	IE, Chrome, Safari
Management Software	Amcrest View Pro, Amcrest Surveillance Pro
Smart Phone	iOS, Android
Camera Features	
White Balance	Auto/Manual
Gain Control	Auto / Manual

Noise Reduction	3D
Motion Detection	Support
Region of Interest	Support
Electronic Image Stabilization	N/A
Defog	N/A
Digital Zoom	16x
Flip	0°/90°/180°/270°

Privacy Masking	Up to 4 areas
Lens	
Lens Type	Fixed
Focal Length	2.8mm
Max. Aperture	F2.0
Angle of View	118°(Diagonal)
Optical Zoom	N/A
Focus Control	Fixed
General	
Power Supply	DC 12V/1.5A, PoE(802.3af)
Power Consumption	<6W(POE)
Operating Conditions	-10°C ~ +50°C Less than 95% RH
Ingress Protection	IP67

Vandal Resistance	N/A
Casing	Metal
Dimensions	6.6" x 3.25" x 2.75"
Net Weight	0.45kg(1 lb)