

IP3M-941

3MP Dual Band WiFi PTZ IP Camera

Technical Specifications

Model	IP3M-941B/W	
Camera		
Image Sensor	1/3" Megapixel progressive scan CMOS	
Effective Pixels	3M (2304x1296)	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual 1/3 (4) ~1/100000	
Min. Illumination	0. 1Lux / F2.2 (Color), 0Lux / F2.2 (IR on)	
S/N Ratio	More than 56dB	
Video Output	N/A	
Camera Features		
Max. IR LEDs Length	10m	
Day/Night	Auto (ICR) / Color / B&W	
Backlight Compensation	BLC / HLC / WDR	
White Balance	Auto / Manual	
Gain Control	Auto / Manual	
Noise Reduction	3D	
Privacy Masking	Up to 4 areas	
Lens		
Focal Length	4mm	
Max Aperture	F2.2	
Focus Control	Manual	
Angle of View	90°	
Lens Type	Fixed lens	
Video		
Compression	H.264H / H.264B / H.264 / MJPEG	
Resolution	3M(2304x1296)/1080P(1920×1080)/ 1.3M(1280x960)/720P(1280×720)/VGA(640x480)	
Frame Rate	Main Stream	3M (2304x1296) 30fps / 1080P / 720p / VGA (1 ~ 30fps)
	Sub Stream	VGA (1 ~ 30fps)
Bit Rate	H.264H: 12K ~ 10240Kbps	
Audio		
Compression	G.711MU, G711A, AAC	
Interface	1 in/ 1 out	
Network		
Ethernet	RJ-45 (10/100Base-T)	
WIFI	2.4GHz (802.11b/g/n) / 5GHz (802.11ac/a/n)	
Protocol	IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP,	

IP3M-941

	SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
Compatibility	ONVIF , CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android
Auxiliary Interface	
Memory Slot	Micro SD
RS485	N/A
Alarm	Alarm in / Alarm out
PIR Sensor Range	N/A
General	
Power Supply	DC5V2A
Power Consumption	< 8W
Working Environment	-10°C~+45°C, Less than 95%RH
Ingress Protection	N/A
Vandal Resistance	N/A
Dimensions	4.13 x 3.94 x 4.93 inches
Weight	0.6 lbs