

Vital Statistics	price, base/ as tested	engine	SAE net power/torque; weight/power	transmission/ gear ratios:1/ maximum test speed, mph/ axle ratio:1	curb weight, pounds	weight distribution, % front/rear	dimensions, inches				fuel tank, gallons	interior volume, cubic feet			suspension				brakes, front/rear	tires
							wheel- base	length	width	height		front	rear	trunk	front	rear	front	rear		
	AUDI A4 3.0 QUATTRO	\$33,665/\$37,690	DOHC 30-valve V-6, 182 cu in (2976cc), aluminum block and heads, Bosch Motronic ME7.0 engine-control system with port fuel injection	220 bhp @ 6300 rpm/ 221 lb-ft @ 3200 rpm; 17.0 lb/hp	6-speed manual/ 3.50, 1.89, 1.32, 1.03, 0.86, 0.73/ 30, 56, 81, 103, 124, 131/ 4.38, limited slip	3750	58.2/41.8	104.3	179.0	69.5	56.2	17.4	49	39	13	ind, 2 diagonal links and 2 lateral links per side, coil springs, anti-roll bar	ind; 1 lower control arm, 1 lateral link, and 1 toe-control link per side; coil springs; anti-roll bar	vented disc/disk; anti-lock control	Dunlop SP Sport 9090, P235/45ZR-17 94Y	
BMW 330i	\$34,635/\$38,972	DOHC 24-valve 6-in-line, 182 cu in (2979cc), aluminum block and head, Siemens MS43 engine-control system with port fuel injection	225 bhp @ 5900 rpm/ 214 lb-ft @ 3500 rpm; 15.0 lb/hp	5-speed manual/ 4.21, 2.49, 1.66, 1.24, 1.00/ 35, 58, 88, 117, 130/ 2.93, limited slip	3377	49.3/ 50.7	107.3	176.0	68.5	55.7	16.6	48	41	11	ind, strut located by a control arm, coil springs, anti-roll bar	ind, 1 trailing arm and 2 lateral links per side, coil springs, anti-roll bar	vented disc/vented disc; anti-lock control	Continental ContiSportContact; F: 225/45ZR-17, R: 245/40ZR-17		
CADILLAC CTS	\$29,990/\$36,765	DOHC 24-valve V-6, 194 cu in (3175cc), aluminum block and heads, Bosch Motronic ME3.11 engine-control system with port fuel injection	220 bhp @ 6000 rpm/ 218 lb-ft @ 3400 rpm; 16.7 lb/hp	5-speed manual/ 3.56, 2.04, 1.34, 1.00, 0.82/ 36, 63, 97, 129, 140/ 3.73	3675	53.6/46.4	113.4	190.1	70.6	56.7	17.5	53	44	13	ind, unequal-length control arms, coil springs, anti-roll bar	ind; 1 lower control arm, 1 lateral link, 1 diagonal link, and 1 toe-control link per side; coil springs; anti-roll bar	vented disc/vented disc; anti-lock control	Goodyear Eagle RS-A, 225/50VR-17		
JAGUAR X-TYPE 3.0	\$38,613/\$39,179	DOHC 24-valve V-6, 181 cu in (2967cc), aluminum block and heads, Denso engine-control system with port fuel injection	231 bhp @ 6800 rpm/ 209 lb-ft @ 3000 rpm; 15.7 lb/hp	5-speed manual/ 3.42, 2.14, 1.45, 1.03, 0.77/ 39, 62, 91, 128, 130/ 3.80	3634	58.9/41.1	106.7	183.9	70.4	54.8	16.0	50	40	16	ind, strut located by a control arm, coil springs, anti-roll bar	ind, 1 trailing arm and 3 lateral links per side, coil springs, anti-roll bar	vented disc/disk; anti-lock control	Continental ContiSportContact, 225/45ZR-17		
LEXUS IS300	\$29,980/\$33,896	DOHC 24-valve 6-in-line, 183 cu in (2997cc), aluminum block and head, Toyota engine-control system with port fuel injection	215 bhp @ 5800 rpm/ 218 lb-ft @ 3800 rpm; 15.7 lb/hp	5-speed manual/ 3.57, 2.06, 1.38, 1.00, 0.85/ 34, 59, 87, 121, 139/ 3.73	3384	53.8/46.2	105.1	176.6	67.9	55.5	17.5	49	35	10	ind, unequal-length control arms, coil springs, anti-roll bar	ind, unequal-length control arms, coil springs, anti-roll bar	vented disc/disk; anti-lock control	Yokohama Radial 376, 205/55VR-16		
LINCOLN LS	\$35,465/\$37,045	DOHC 24-valve V-6, 181 cu in (2967cc), aluminum block and heads, Ford EEC-V engine-control system with port fuel injection	210 bhp @ 6500 rpm/ 205 lb-ft @ 4750 rpm; 17.6 lb/hp	5-speed manual/ 4.23, 2.52, 1.66, 1.22, 1.00/ 38, 63, 96, 129, 130/ 3.07	3690	51.4/48.6	114.5	193.9	73.2	56.1	18.0	58	46	14	ind, unequal-length control arms, coil springs, anti-roll bar	ind, unequal-length control arms with a toe-control link, coil springs, anti-roll bar	vented disc/vented disc; anti-lock control	Michelin MXM4, 235/50VR-17		
SAAB 9-3 VIGGEN	\$38,593/\$40,235	turbocharged and intercooled DOHC 16-valve 4-in-line, 140 cu in (2290cc), iron block and aluminum head, Saab Trionic 7 engine-control system with port fuel injection	230 bhp @ 5500 rpm/ 258 lb-ft @ 2500 rpm; 14.0 lb/hp	5-speed manual/ 3.38, 1.76, 1.18, 0.89, 0.66/ 33, 63, 94, 124, 151/ 4.05	3219	61.4/38.6	102.6	180.9	67.4	55.7	17.0	50	39	22	ind, strut located by a control arm, coil springs, anti-roll bar	ind, trailing arms integral with a transverse member, coil springs, anti-roll bar	vented and grooved disc/vented and grooved disc; anti-lock control	Pirelli P6000, 215/45ZR-17		