

	price, base/ as tested	engine/transmission	SAE net power/torque; weight/power	exterior dimensions, inches				curb weight, pounds	weight distribu- tion, % F/R	fuel tank, gallons	passenger- area volume, front/rear, cubic feet	cargo volume, seats up/folded, cubic feet	what fits in back			suspension		brakes, F/R	tires
				wheel- base	length	width	height						# beer cases, seats up/ folded, cu ft	length of pipe, inches	sheet of plywood, inches (l x w)				
																front	rear		
<b>CHRYSLER PT CRUISER</b>	\$16,840/ \$18,015	2429cc DOHC 16-valve 4-in-line, iron block and aluminum head, port fuel injection/5-speed manual	150 bhp @ 5200 rpm/ 162 lb-ft @ 4000 rpm; 21.3 lb/bhp	103.0	168.8	67.1	63.0	3189	58.5/41.5	15.0	52/49	19/64*	11/29*	114.0	60 x 37	ind, strut located by a control arm, coil springs, anti-roll bar	rigid axle integral with 2 trailing arms and an anti-roll bar, Watt's linkage, coil springs, anti-roll bar	vented disc/ disc; anti-lock control	Goodyear Eagle LS, P195/65TR-15
<b>FORD FOCUS ZX5</b>	\$16,355/ \$18,330	1987cc DOHC 16-valve 4-in-line, iron block and aluminum head, port fuel injection/5-speed manual	130 bhp @ 5300 rpm/ 135 lb-ft @ 4500 rpm; 21.1 lb/bhp	103.0	168.1	66.9	56.3	2746	61.1/38.9	13.2	53/45	19/43	9/23	109.0	54 x 40	ind, strut located by a control arm, coil springs, anti-roll bar	ind, trailing arm located by 3 lateral links, coil springs, anti-roll bar	vented disc/ disc; anti-lock control	Firestone Firehawk GTA, P205/50HR-16
<b>MAZDA PROTEGÉ5</b>	\$16,905/ \$18,485	1991cc DOHC 16-valve 4-in-line, iron block and aluminum head, port fuel injection/5-speed manual	130 bhp @ 6000 rpm/ 135 lb-ft @ 4000 rpm; 21.5 lb/bhp	102.8	170.5	67.1	57.8	2795	59.3/40.7	14.5	51/41	20/24	9/18	117.0	61 x 37	ind, strut located by a control arm, coil springs, anti-roll bar	ind, strut located by 1 trailing link and 2 lateral links, coil springs, anti-roll bar	vented disc/ disc; anti-lock control	Dunlop SP Sport 5000M, P195/50VR-16
<b>PONTIAC VIBE</b>	\$16,900/ \$20,000	1794cc DOHC 16-valve 4-in-line, aluminum block and head, port fuel injection/5-speed manual	130 bhp @ 6000 rpm/ 125 lb-ft @ 4200 rpm; 21.4 lb/bhp	102.4	171.9	69.9	62.2	2778	58.2/41.8	13.2	50/43	25/57	9/28	112.0	64 x 38	ind, strut located by a control arm, coil springs, anti-roll bar	ind, trailing arms integral with a transverse member, coil springs, anti-roll bar	vented disc/ drum; anti-lock control	Goodyear Eagle RS-A, P205/55HR-16
<b>SUZUKI AERIO SX</b>	\$14,999/ \$15,499	1995cc DOHC 16-valve 4-in-line, aluminum block and head, port fuel injection/5-speed manual	141 bhp @ 5700 rpm/ 135 lb-ft @ 3000 rpm; 19.5 lb/bhp	97.6	166.5	67.7	61.0	2747	59.3/40.7	13.2	52/42	21/64	10/24	115.0	57 x 34	ind, strut located by a control arm, coil springs, anti-roll bar	ind, strut located by 1 trailing link and 2 lateral links, coil springs, anti-roll bar	vented disc/ drum; anti-lock control	Yokohama Geolandar GO46, P195/55VR-15
<b>TOYOTA MATRIX XRS</b>	\$19,235/ \$19,705	1796cc DOHC 16-valve 4-in-line, aluminum block and head, port fuel injection/6-speed manual	180 bhp @ 7600 rpm/ 130 lb-ft @ 6800 rpm; 15.8 lb/bhp	102.4	171.3	69.9	61.0	2847	58.7/41.3	13.2	52/44	22/53	9/28	112.0	64 x 38	ind, strut located by a control arm, coil springs, anti-roll bar	ind, trailing arms integral with a transverse member, coil springs, anti-roll bar	vented disc/ disc; anti-lock control	Firestone Firehawk SZ50, P215/50ZR-17