

	price, base/ as tested	engine	SAE net power/torque	transmission/ gear ratios:1/ maximum speed in gears, mph/ axle ratio:1	curb weight, pounds	weight distribution, % front/rear	dimensions, inches				fuel tank, gallons	interior volume, cubic feet		suspension		brakes, front/rear	tires
							wheel- base	length	width	height		front	trunk	front	rear		
CHEVROLET CORVETTE Z06	\$48,920/ \$48,946	pushrod 16-valve V-8, 346 cu in (5665cc), aluminum block and heads, GM engine-control system with port fuel injection	385 bhp @ 6000 rpm/ 385 lb-ft @ 4800 rpm	6-speed manual/ 2.97, 2.07, 1.43, 1.00, 0.84, 0.56/ 48, 69, 100, 143, 168, 155/ 3.42, limited slip	3126	53.5/46.5	104.5	179.7	73.6	47.7	18.5	52	13	ind, unequal-length control arms, transverse plastic leaf spring, anti-roll bar	ind, unequal-length control arms with a toe-control link, transverse plastic leaf spring, anti-roll bar	vented disc/ vented disc; anti-lock control	Goodyear Eagle F1 Supercar; F: 265/40ZR-17 91Y, R: 295/35ZR-18 91Y
DODGE VIPER GTS ACR	\$85,268/ \$88,814* (2000)	pushrod 20-valve V-10, 488 cu in (7990cc), aluminum block and heads, Chrysler JTEC engine-control system with port fuel injection	460 bhp @ 5200 rpm/ 500 lb-ft @ 3700 rpm	6-speed manual/ 2.66, 1.78, 1.30, 1.00, 0.74, 0.50/ 54, 81, 111, 145, 186, 140/ 3.07, limited slip	3450	48.8/51.2	96.2	176.7	75.7	47.0	18.5	49	9	ind, unequal-length control arms, coil springs, anti-roll bar	ind, unequal-length control arms with a toe-control link, coil springs, anti-roll bar	vented disc/ vented disc*	Michelin Pilot Sport Radial X; F: 275/35ZR-18, R: 335/30ZR-18
FORD SVT MUSTANG COBRA R	\$55,675/ \$56,715 (2000)	DOHC 32-valve V-8, 330 cu in (5409cc), iron block and aluminum heads, Ford EEC-V engine-control system with port fuel injection	385 bhp @ 6250 rpm/ 385 lb-ft @ 4250 rpm	6-speed manual/ 2.97, 2.07, 1.43, 1.00, 0.80, 0.62/ 46, 67, 97, 138, 177, 170/ 3.55, limited slip	3580	56.4/43.6	101.3	183.5	73.1	52.2	20.0	50	11	ind, strut located by a control arm, coil springs, anti-roll bar	ind, unequal-length control arms with a toe-control link, coil springs, anti-roll bar	vented disc/ vented disc; anti-lock control	BFGoodrich g-Force T/A, 265/40ZR-18 97Y