

	price, base/ as tested	engine	SAE net power/torque; weight/power	transmission/ gear ratios:1/ maximum test speed, mph/ axle ratio:1	curb weight, pounds	weight distribution, % front/rear	dimensions, inches				fuel tank, gallons	interior volume, cubic feet			suspension		brakes, front/rear	tires
							wheel- base	length	width	height		front	rear	trunk	front	rear		
<b>FORD SVT FOCUS</b>	\$17,995/ \$19,265	DOHC 16-valve 4-in-line, 121 cu in (1988cc), iron block and aluminum head, Ford EEC-V engine-control system with port fuel injection	170 bhp @ 7000 rpm/ 145 lb-ft @ 5500 rpm; 16.5 lb/bhp	6-speed manual/ 4.44, 2.67, 1.33, 1.08, 1.33, 1.08/ 42, 69, 94, 116, 135, 135/ 2.88 (I, II, V, VI); 4.25 (III, IV)	2800	61.0/39.0	103.0	168.1	66.9	56.3	13.2	53	45	19	ind, strut located by a control arm, coil springs, anti-roll bar	ind, 1 trailing arm and 3 lateral links per side, coil springs, anti-roll bar	vented disc/ disc; anti-lock control	Continental ContiSport- Contact, 215/45WR-17
<b>HONDA CIVIC Si</b>	\$19,000/ \$19,000 (est)	DOHC 16-valve 4-in-line, 122 cu in (1998cc), aluminum block and head, Honda PGM-FI engine-control system with port fuel injection	160 bhp @ 6500 rpm/ 132 lb-ft @ 5000 rpm; 17.1 lb/bhp	5-speed manual/ 3.06, 1.77, 1.21, 0.92, 0.74/ 32, 56, 82, 107, 125/ 4.76	2740	62.0/38.0	101.2	165.6	66.7	56.5	13.2	49	36	16	ind, strut located by a control arm, coil springs, anti-roll bar	ind, 1 trailing arm and 2 lateral links per side, coil springs, anti-roll bar	vented disc/ disc; anti-lock control	Michelin MXV4, 195/60VR-15
<b>VOLKSWAGEN GTI 1.8T</b>	\$19,460/ \$22,000	turbocharged and intercooled DOHC 20-valve 4-in-line, 107 cu in (1781cc), iron block and aluminum head, Bosch Motronic ME7.5 engine-control system with port fuel injection	180 bhp @ 5500 rpm/ 174 lb-ft @ 1950 rpm; 16.1 lb/bhp	5-speed manual/ 3.30, 1.94, 1.31, 1.03, 0.84/ 38, 65, 97, 123, 131/ 3.65	2900	61.4/38.6	98.9	164.9	68.3	56.7	14.5	50	38	18	ind, strut located by a control arm, coil springs, anti-roll bar	trailing arms integral with a transverse member, coil springs, anti-roll bar	vented disc/ disc; anti-lock control	Michelin Pilot MXM4, 225/45HR-17