

Pump and **T**reet

Pushing the Limits of Sustainable
Remediation Practices


Karah Conklin, P.E.

March 18, 2025


AEHS West Coast Conference



Sustainable and Resilient Remediation



Integrating Resilience and Sustainability into the Remedial Project Life Cycle



Sustainable Remediation Limitations

- › Site accessibility
- › Timeframes
- › Incomplete degradation
- › Limited range of contaminants treated
- › O&M requirements
- › Uncertainty of natural systems

Common Sustainable Remediation Technologies

› Bioremediation

› Constructed Treatment Wetlands

› Phytotechnologies

› Permeable Reactive Barriers

› In Situ Remediation

› Soil Vapor Extraction/Sparging

› Solidification and Stabilization (S/S)

› Vegetated Soil Covers


Phytotechnologies



*The use of **plants** to remediate soil and water*




What can we treat?



STRENGTHS



- › Often passive
- › Low O&M
- › Long life
- › High PR
- › Aesthetically pleasing
- › Cost effective



- › Ability to access contamination
- › Long remediation timeframes (and thus longer O&M)
- › Phytotoxicity
- › Land use limitations


LIMITATIONS

Former Wood Treating Facility - Mississippi




Site Background

- › 90-acre Former Wood-treating Facility
- › Operated from 1928 to 2003
- › Primary COCs in groundwater are PAHs. Primary impacts are in deeper aquifer.
- › Preferred remedy at the Site is hydraulic control using phytoremediation



Concerns for Groundwater Remediation

- › Limited Site utilities
- › Low O&M budget
- › Significant amount of precipitation occurs in non-growing months
- › Target groundwater is at >20 feet bgs. Shallow groundwater at 5-6 feet bgs.
- › Soils are mostly clay-based




-




Pump and Treet Pilot Study

- Installed approximately 560 trees in a 125-foot by 50-foot area in 2021
- Utilized a solar driven pumping system to extract groundwater and gravity irrigated trees during the growing season.



Results and Observations

- › Trees were average of 9 feet tall at the end of Year 1 and 17 feet at the end of Year 2



Results and Observations

- › Trees were average of 9 feet tall at the end of Year 1 and 17 feet at the end of Year 2
- › Shallow groundwater levels decreased by 1.5 after 1 full growing season
- › DN-19 hybrid poplar trees held onto their leaves longer than the OP-367 hybrid poplars



OP-367





DN-19


Results and Observations

- › Trees were average of 9 feet tall at the end of Year 1 and 17 feet at the end of Year 2
- › Shallow groundwater levels decreased by 1.5 after 1 full growing season
- › DN-19 hybrid poplar trees held onto their leaves longer than the OP-367 hybrid poplars
- › No accumulation of PAHs in soil and no increase in PAHs in shallow groundwater
- › O&M for solar pumping system was ~2-3 hours per week


Vegetated Landfill Covers



Cover Differences



Conventional Cover




Water Balance Cover

STRENGTHS



- › Cost-effective
- › Lower maintenance
- › Enhanced erosion resistance
- › Improved aesthetics and land use options
- › Potential for water infiltration reduction



- › Generally more applicable in arid or semi-arid climates
- › Root penetration into waste (exposure)
- › Nutrient and soil quality concerns
- › Reliability under extreme weather events
- › Limited methane management options

LIMITATIONS

Former Dye- Manufacturing Facility – New York



Former Dye-Manufacturing Facility – New York

- › 9 acre landfill utilized for industrial waste from facility
- › Operated from 1978 until 2001
- › Waste included solvents, dye waste, zinc oxide, chromium hydroxide, debris/lab waste



Former Dye-Manufacturing Facility – New York

Groundwater extraction and treatment

- › Metals – aeration, GAC, and metals adsorption
- › VOCs – air stripping, vapor and liquid phase GAS
- › DO injection system

Issues/Concerns

- › Significant O&M required
- › Did not address direct exposure
- › Did not address continued groundwater contamination

Former Dye-Manufacturing Facility – New York


Initial Remediation Approach

- Groundwater extraction and treatment:
 - Metals – aeration, GAC, and metals adsorption
 - VOCs – air stripping, vapor and liquid phase GAS
 - DO injection system



Final Remedial Approach

- Vegetated evapotranspiration landfill cover
- Perimeter groundwater collection system, augmented with phytoremediation
- Drainage swales to redirect precipitation

Soil Cover/Cap in New York




Constructed Treatment Wetlands



What can we treat?

Engineered treatment system designed to achieve water quality improvements by maximizing processes that occur in natural wetlands


- › Mine Drainage
- › Sanitary Wastewater
- › Landfill Leachate
- › Agricultural Runoff
- › Airport Runoff
- › Urban and Industrial Stormwater
- › Industrial Wastewater
- › Groundwater Remediation
- › Metals
- › Nutrients
- › Solids
- › PCBs
- › BTEX
- › PAHs
- › Chlorinated Solvents
- › Glycol
- › BOD
- › pH
- › TSS



STRENGTHS



- › Cost-effective
- › Lower maintenance
- › Low energy requirements
- › Improved aesthetics
- › Adaptable for varying flows



- › Large areas required
- › Treatment limitations
- › Climate sensitivity
- › Exposure concerns
- › Reliability under extreme weather events



LIMITATIONS

Active Oil and Gas Development Facility - Colorado



Site Background

- › 1MGD produced water pond from oil well production
- › Bench scale evaluation
- › Toxicity, alkalinity, PAHs, and temperature issues for discharge



Pilot System

- › Utilized an aerated, compost and gypsum-based wetland to treat PAHs and general toxicity
- › Aeration provided by solar panel system
- › Hydraulics run by gravity



Pilot System

- › System met ALL NPDES discharge criteria, including temperature
- › Full-scale system being designed
- › Projected to save client over \$1M annually vs GAC treatment AND got client out of compliance NOV/C&D




Textile Manufacturing Facility - Virginia



Site Background

- › PCB in soil beneath plant due to historical PCB spill
- › Infiltration into the storm sewer system led to PCB exceedances in stormwater discharge




PCB Minimization Strategy

- › Stormwater diversion away from impacted areas
- › Storm sewer rehabilitation and lining
- › End of Pipe Treatment
 - Minimal space available
 - Large rain events
 - Hard to maintain




Natural Media Filtration and Constructed Wetland



Compost NMF for PCB removal

- › Filtration
- › Adsorption
- › Reductive Dechlorination

Bench Scale



Field Pilot



Summary

- › As sustainable remediation technologies have matured, practitioners now have greater opportunities to push the boundaries of these methods.
- › These approaches can be adapted to diverse challenges and offer valuable insights for future advancements in the field.





integral

Karah Conklin, P.E.

307.351.6868

kconklin@integral-corp.com