

Applied Motion Products, Inc. 404 Westridge Dr. Watsonville, CA 95076, USA 1-800-525-1609 Tel (831) 761-6555

### **Product Datasheet**

www.Applied-Motion.com

# 23PL010

NEMA 23 Planetary Gearhead



#### **Product Features**

- True planetary design
- Low backlash design
- High strength steels
- High shaft loading capacity
- Sealed ball bearings
- Heat treated gears
- High efficiency design

### Description

The 23PL010 planetary gearhead offers true planetary performance in a high torque, low backlash design. High strength, heated treated gears provide for efficient transmission of torque and accurate speed matching.

## Specifications

Part Number:	23PL010
Frame Size:	NEMA 23
Ratio:	10:1
Torque, Nominal:	119 in-lb
Torque, Max Accel:	179 in-lb
Length:	2.66 inches
Weight:	1.8 lbs
Input Speed:	6500 rpm max
Backlash:	6
Low Backlash:	3
Operating	-50 to 120 °C
Temperature:	
Service Life:	> 10,000 hours
Efficiency:	90%
Inertia:	5.471E-05 oz-in-sec <sup>2</sup>

## Downloads

Product PDF - S3 Link:	http://s3.amazonaws.com/applied-motion-pdf/23PL010.pdf
2D Drawing:	
3D Drawing:	□ <u>23PL-1STG.stp</u> <u>23PL-1STG.zip</u>

# Products in the Series PL Gearheads

Part Number 🗘 🗘	Frame Size 🗘 🗘	Ratio 🗘	Length 🛟	Output Torque 🗘	Backlash 🛟	1pc. 🛟
<u>17PL010</u>	NEMA 17	10:1	2.62	56	6	\$811.00
<u>23PL004</u>	NEMA 23	4:1	2.66	360	6	\$811.00
<u>23PL005.5</u>	NEMA 23	5.5:1	2.66	317	6	\$811.00
<u>23PL010</u>	NEMA 23	10:1	2.66	119	6	\$811.00
<u>23PL028</u>	NEMA 23	28:1	3.48	384	10	\$1052.00
<u>23PL070</u>	NEMA 23	70:1	3.48	288	10	\$1052.00
<u>23PL100</u>	NEMA 23	100:1	3.48	110	10	\$1052.00
<u>34PL004</u>	NEMA 34	4:1	4.19	1219	6	\$1273.00
<u>34PL005.5</u>	NEMA 34	5.5:1	4.19	1113	6	\$1273.00
<u>34PL010</u>	NEMA 34	10:1	4.19	552	6	\$1273.00
<u>34PL028</u>	NEMA 34	28:1	5.31	1346	10	\$1589.00
<u>34PL070</u>	NEMA 34	70:1	5.31	1027	10	\$1589.00
<u>34PL100</u>	NEMA 34	100:1	5.31	507	10	\$1589.00