

**CONDENSING GAS TANKLESS with  
X3<sup>®</sup> SCALE PREVENTION**

An expert in both water heating and treatment, Reliance<sup>®</sup> has combined the two technologies to achieve unparalleled scale protection. Now available on our condensing gas tankless water heaters.

- **X3 Scale Prevention Technology**
  - Extends the life of the unit up to 3x longer\*
  - Eliminates the need for regular scale-related maintenance
  - No warranty exclusion for hard water
  - Maintains “like-new” performance longer
- **15-Year Limited Warranty** on heat exchanger  
**5-Year Limited Warranty** on all parts
- **Available in Indoor and Outdoor models**
- **Ultra-Low NOx emissions**
- **ENERGY STAR<sup>®</sup>**  
Qualifies for many state and local utility rebates\*\*
- **Safety Features**
  - Exhaust & Water Temperature Safety Control
  - Overheat Cut-Off Fuse
  - Air-Fuel Ratio (AFR) Sensor

**MORE FEATURES ON BACK**

\*Compared to other tankless models without X3 Technology

\*\*Select models



## MORE FEATURES (continued from front)

- **Power Direct Vent Design:**  
Flexible venting with PVC, CPVC, polypropylene, or ABS Pipe for intake and exhaust (solid core only)  
Category III or IV venting can be used  
Exhaust, 3" PVC up to 70'; 4" PVC up to 100'
- Internal Freeze Protection System
- Durable Heat Exchanger
- 3/4" NPT Connections



## EASY-TO-USE ELECTRONIC DISPLAY

- User Friendly, Easy to Read, Eye-level Display
- Display features:
  - On/Off button
  - Temperature Setting buttons
  - Info and Operation Status
  - Quick-Read Water Temperature

## CONDENSING GAS TANKLESS with X3® SCALE PREVENTION TECHNOLOGY

Model Number	Type	Gas Consumption Input (BTU/Hour)		UEF	Maximum GPM*	Dimensions In Inches			
		Minimum	Maximum			Height	Width	Depth	Height w/Cartridge
<b>INDOOR MODELS</b>									
TS-540X3-GIH 100	Natural	15,000	199,000	0.93	10	23 5/8	17 3/4	11 1/4	35 9/16
TS-540X3-LIH 101	Propane	13,000	199,000	0.93	10	23 5/8	17 3/4	11 1/4	35 9/16
TS-340X3-GIH 100	Natural	15,000	180,000	0.95	8	23 5/8	17 3/4	11 1/4	35 9/16
TS-340X3-LIH 101	Propane	13,000	180,000	0.95	8	23 5/8	17 3/4	11 1/4	35 9/16
TS-240X3-GIH 100	Natural	15,000	160,000	0.94	6.6	23 5/8	17 3/4	11 1/4	35 9/16
TS-240X3-LIH 101	Propane	13,000	160,000	0.94	6.6	23 5/8	17 3/4	11 1/4	35 9/16
<b>OUTDOOR MODELS</b>									
TS-540X3-GEH 100	Natural	15,000	199,000	0.95	10	23 5/8	17 3/4	11 1/4	35 9/16
TS-540X3-LEH 101	Propane	13,000	199,000	0.95	10	23 5/8	17 3/4	11 1/4	35 9/16
TS-340X3-GEH 100	Natural	15,000	180,000	0.94	8	23 5/8	17 3/4	11 1/4	35 9/16
TS-340X3-LEH 101	Propane	13,000	180,000	0.94	8	23 5/8	17 3/4	11 1/4	35 9/16
TS-240X3-GEH 100	Natural	15,000	160,000	0.95	6.6	23 5/8	17 3/4	11 1/4	35 9/16
TS-240X3-LEH 101	Propane	13,000	160,000	0.95	6.6	23 5/8	17 3/4	11 1/4	35 9/16

### ENERGY STAR® Qualified Models

15-150 PSI Water Pressure. 40 PSI or above recommended for maximum flow.

\*Current numbers based on factory testing; 0.5 GPM for activation, 0.4 GPM required for continuous fire after initial ignition.

Indoor models are certified from sea level to 10,000 ft. elevation. Outdoor models are certified from sea level to 6,000 ft elevation.

For complete information consult written warranty.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches.

Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement.

Some models may not be available in all markets.



# Reliance®

Water Heaters

### RELIANCE® WATER HEATERS

www.RelianceWaterHeaters.com

500 Tennessee Waltz Pkwy., Ashland City, TN 37015, 1-800-365-4054

©2023 Reliance Water Heaters. All rights reserved.

RX3CSS0823