




## STEP-BY-STEP INSTRUCTIONS I Page 1



 Score all dashed lines to make folding easier. Tracing over dashed lines with a ruler and an empty ball-point pen works well. Press into the paper for best results.




Cut out the shapes including the tabs.A hobby knife is more accurate than scissors.



3. Be sure to cut out the area between the fenders and hood as shown.



4. Be sure to cut out the area between the fenders and rear bars as shown.



5. The tires should look like this.



6. Fold along every scored line for all pieces as shown.

## STEP-BY-STEP INSTRUCTIONS | Page 2



7. Fold along every scored line for all pieces as shown.




8. Fold along every scored line for all pieces as shown.



9. Glue the tab on the end of the tread to the opposite side creating a loop.



10. Put glue on the inside of the tire all the way to the edges.



11. Fold the facade up and move the tread around until it fits the shape of the tire.




12. Repeat with the opposite side.


## STEP-BY-STEP INSTRUCTIONS | Page 3




13. Put glue on the area shown above at the back of the roof.




14. Press together as shown.




15. Glue the front section of the Talon to the roof as shown.



16. It should look like this.




17. Glue the tabs on the back to the inside of the rear panels.




18. The bottom-rear corner should look like this.

## STEP-BY-STEP INSTRUCTIONS | Page 4



 Glue the tab on the fenders to its corresponding glue icon on the side of the Talon.



20. Repeat on the opposite side.




21. Glue all the front tabs on one side first.



22. Press the hood and grille onto the tabs with the fenders hanging loose at the sides.





23. Glue the tab on the fenders to its corresponding glue icon on the side of the Talon. Repeat on the opposite side.



24. Attach the wheels to the semi-circles on each fender. The semi-circles approximate the correct location, so they only have to be covered slightly by the tires.

# STEP-BY-STEP INSTRUCTIONS I Page 5







26. They should look like this once attached.



27. Photograph and share!