



2026 HELP Loan Equipment Availability List

Suffolk County Soil and Water Conservation District is pleased to announce the availability of the following equipment for loan. HELP Equipment Loan service is FREE to all Suffolk County residents! Please read all information contained in this packet prior to scheduling.

Important Information:

- ALL Equipment must be placed on a flatbed and cannot be towed behind vehicles! No exceptions. A towing company is recommended for transportation if you lack the required equipment.
- Equipment is rented for (7) days at a time. If equipment is needed for longer, please let staff know and we will try our best to accommodate you. We cannot guarantee equipment availability over (7) consecutive days.
- A loan contract must be completed prior to machine pick-up.
- \$500 check deposit is required at pick-up and is returned upon return and inspection of equipment by SWCD Staff.
- Equipment must be returned CLEAN and undamaged. If not, some or all your deposit will be forfeited.
- Please note that a new contract needs to be completed for each loan period. If 'Additionally Insured' paperwork is out-of-date, an updated form needs to be provided as well.
- Be mindful that there are other residents who may have pre-booked, early booking is strongly recommended!
- Program participants are expected to be reachable by phone and remain communicative with staff members. This ensures that transfer of equipment between farms goes smoothly and on schedule.
- If you are unsure of what equipment you need, reach out, we can assist you!

Contact for additional information: SWCD Main Office (631)852-3825

Please send all questions and loan requests to swcdinfo@suffolkcountyny.gov

Millcreek Row Mulcher 406



Specifications: Side discharge bulk material spreader. 5.4 heaped cubic yard capacity, PTO driven, 2 floor apron speeds. Includes cleated belt cross conveyor. PTO.

Dimensions: 62"W X 16'10"L

Minimum Tractor HP Required: 30hp

New Holland Model 145



Specifications: Struck Level Capacity 110 Cu.ft, Shear Bolt Protected Apron Chain, Adjustable Swing Away Jack, Single Beater, Heaped Capacity 182 Cu.Ft, 295/75R Retread Tires, Hydraulic End Gate, Splash Guard.

Dimensions: 92.5"W X 196.75"L

Minimum Tractor HP Required: 40hp

Unverferth Zonebuilder 132 (4 Shank)



Specifications: 3pt 4 Shank Zone-Builder. Rigid, auto reset shanks. 30" spacing, 20" blades. The straight leg shank design rips through compaction up to 20" deep with minimal surface disturbance, allowing plant roots to reach moisture and nutrients deeper in the soil. Points and wear-bars are heat-treated cast, and the double-frame all-welded construction ensures long-term performance. It can be easily modified by removing shanks.

Dimensions: Variable, please contact us for more information.

Minimum Tractor HP Required: 30-50hp PER shank (Please reach out to us for clarification)

TruAx FlexII 88-SS No Till Grain Drill



Specifications: No till, Grain drill, standard grass cool season box, Mechanical Acre meter, parking stands, tail lights, folding tongue, spare tire lockable mount.

Dimensions: 8.3' W X 12'L

Minimum Tractor HP Required: 40hp

ABI Manual Manure Spreader 50c



Specifications: The 50 cu. ft. (Heaped Capacity) ground-driven ABI Manure Spreaders feature an advanced design that SHREDS manure, controls application flow, and evenly applies manure to the ground. It is constructed of extremely thick corrosion-resistant 12-gauge COR-TEN steel (Copper Chromium Alloy). The box is coated with an internal protective industrial liner. The apron chain/web is stainless steel for an extremely long life. The floor is made of lifetime poly lumber, and the spreader is finished with a thick premium protective 2-ply coating. 4-Speed Application Flow Control empowers operators to control manure application.