



Serial PCI Express Card

2 Ports, x1 Lane

Part No.: [158169](#)

EAN-13: 0766623158169 | UPC: 766623158169

PCI Express balances cost, performance, compatibility and advanced features for computing platforms.

The Manhattan Serial PCI Express Card quickly and easily adds two DB9 ports to PCI Express-enabled desktop systems to connect and communicate with serial peripheral devices.

Fast Data Transfer

The Manhattan Serial PCI Express Card can be configured to achieve baud rates of up to 230,400 bps to take advantage of PCI Express data transfer speeds of up to 2.5 Gbps. Compliance with PCI Express 1.1 specifications ensures that most PCI ExpressCard-equipped desktop computers and devices can operate at peak performance.

Simple Installation

The Manhattan Serial PCI Express Card fits PCI Express x1, x4, x8 and x16 lane buses, and configurable COM port settings provide a flexible way to customize its use to various needs.

Features:

- Easily adds two configurable serial ports to a desktop computer
- Fits PCI Express x1, x4, x8 and x16 lane buses
- Fits standard and low-profile PCI slots
- Plug-and-play installation; hot-swappable; Windows compatible
- Three-Year Warranty

Specifications:

Standards and Certifications

- PCI Express 1.1
- PCI Power Management 1.2
- CE
- FCC

Port Specifications

- 2 DB9 male ports

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Programmable baud rate of up to 230,400 bps
- Oxford serial chipset
- Single 3.3V operation
- 128-Byte transmit/receive FIFO
- Compatible with 16C950

Bus Specifications

- PCI Express x1
- Bus speed: 2.5 Gbps
- Compliant with PCI Express 1.1 specifications
- Compliant with PCI Power Management 1.2 specifications

Physical

- Dimensions (with regular bracket): 12 x 6.8 x 2 cm (4.7 x 2.6 x 0.8 in.)
- Weight (with regular bracket): 53.8 g (1.9 oz.)

System Requirements

- Windows XP/Server 2003/Vista/7/8
- PCI Express-enabled system with an available PCI Express slot
- CD-ROM drive

Package Contents

- Serial PCI Express Card
- 2 low-profile brackets
- Instructions and driver CD



