



Professional Video Splitter

8-Port, VGA, SVGA, MultiSync

Part No.: [207355](#)

EAN-13: 0766623207355 | UPC: 766623207355

Easily distribute a single VGA signal to multiple displays.

The Manhattan Professional Video Splitter with built-in booster streams a single VGA signal from a personal computer or other VGA-equipped source to up to eight displays. Ideal for trade shows, classrooms, video conferencing and presentations and retail applications, the Manhattan Professional Video Splitter is a good choice for splitting and distributing a signal to multiple displays when source equipment is remotely stored in a secured room or cabinet. Cascade multiple units up to three levels to output VGA signals to additional displays in widely distributed applications. The gold-plated contacts and fully shielded metal case ensure reliable signal transmission with less degradation.

Features:

- Duplicates a single VGA signal for up to eight VGA outputs
- Supports VGA bandwidths up to 350 MHz and resolutions up to 1920 x 1680 with effective transmission distance up to 65 m (210 ft.)
- Delivers a clear, sharp signal from a PC to VGA, SVGA and MultiSync displays, projectors and more
- Cascade up to three levels to expand signal distribution to more displays
- Automatic power save helps conserve power until VGA signal is restored
- Easy to install: requires no configuration
- Three-Year Warranty

Specifications:

Standards and Certifications

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- FCC
- CE
- ISO 9002

General

- LED indicator: Power (green)
- Cable length, maximum: 65 m (210 ft.)
- Connector input: HD15 male; output: HD15 female (8)
- Power adapter: 9 VAC, 300 mA

Signal

- Signal bandwidth: 350 MHz
- Signal type: VGA, SVGA, MultiSync
- Input voltage, minimum: 0.5 V p-p
- Input voltage, maximum: 1.0 V p-p
- I/O impedance: 75 Ohm

Resolution

- Resolution: 1920 x 1680
- Horizontal frequency: 30 – 120 kHz
- Vertical frequency: 40 – 120 Hz

Ports

- HD15 male
- HD15 female (8)
- Power port: 9 V, 1000 mA

Physical

- Enclosure: metal
- Dimensions: 203 x 103 x 42 mm (8 x 4 x 1.65 in.)
- Weight: 694 g (24.5 oz.)

Package Contents

- Professional Video Splitter
- Instructions



