



Mini-DVI to VGA Adapter

Mini-DVI Male to VGA Female

Model
308489

Easily connects a mini-DVI source with a VGA cable.

The MANHATTAN® Mini-DVI to VGA Adapter establishes a fast and convenient connection between a media source equipped with a mini-DVI port and a VGA display cable. This single cable solution keeps installations and workplaces neat and orderly and requires no external power supplies or complicated configuration making it ideal for presentations, retail displays, trade events, training and more. Gold-plated contacts and full shielding help MANHATTAN Mini-DVI adapters provide clear and stable video transmissions. Durable white PVC jackets and molded boots with strain relief complement Macintosh systems and help ensure connections remain uninterrupted and steady.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.



REV.	DESCRIPTION	ENG.	APPROVAL

ELECTRICAL PROPERTIES:

- 100% OPEN SHORT MIS-WIRE TEST
- Contact Resistance: 10 ohm
- Insulation Resistance: 5M ohm
- Hi-POT: 300V AC/10ms

HD15F	MINI DV132P
1	24
2	22
3	20
6	32
7	30
8	28
9	17.25
10	9-10
12	18
13	29
14	31
15	26
SHELL	SHELL

No.	DESCRIPTION	UNIT	QTY
4	PVC 66P WHITE IN COLOR	PCS	1
3	HIGH DENSITY 18P FEMALE SOLDER INSULATOR COLOR BLACK SHELL NICKEL	PCS	1
2	UL26276 32#/3COAX+30#/6C+AB IPOD WHITE IN COLOR OD:5.5	PCS	1
1	MINI-DVI32P GRAY 725238H CONTACT:G/F SHELL PLATED:NICKEL ABS SHELL IPOD WHITE	PCS	1

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF MANHATTAN AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF MANHATTAN.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE:±0.2°

TOLERANCE (MM)	TOLERANCE (MM)
0-1.0	±0.20
1.0-3.0	±0.30
3.0-6.0	±0.40
6.0-12.0	±0.50
12.0-25.0	±0.60
25.0-50.0	±0.70
50.0-100.0	±0.80
100.0-150.0	±0.90
150.0-200.0	±1.00
200.0-300.0	±1.20
300.0-500.0	±1.50
500.0-1000.0	±2.00

MANHATTAN

TITLE: MH P/N: 308489

APPROVED: [Signature]

DATE: [Date]

DESIGNED BY: [Name]

CHECKED BY: [Name]

DATE: [Date]

SCALE: 1:1

REV: A

Features

- Connects a mini-DVI source to VGA display cable
- Delivers a single, high-quality signal to a VGA display – ideal for Mac computers
- Fully shielded to reduce EMI and other interference sources
- Gold-plated connectors provide maximum connectivity
- Molded PVC boot and strain relief
- Lifetime Warranty

Specifications

STANDARDS AND CERTIFICATIONS

- UL
- DVI

CONTACTS

- Mini-DVI-D 32-pin male
- HD 15-pin female
- Gold-plated
- Molded PVC boot
- Shielded

CABLE

- 30 and 32 AWG connectors
- Mylar and aluminum shielding
- Withstanding voltage: 300 VDC

- Insulation resistance: 5 MOhms
- Conductive resistance: 10 Ohms
- Thermal plastic casing
- Length: 20 cm (7.9 in.)
- Weight: 31.2 g (1.1 oz.)

PACKAGE CONTENTS

- Mini-DVI Male to VGA Female Adapter

For more information on MANHATTAN products, consult your local dealer or visit www.manhattan-products.com.


MANHATTAN
BRINGING COMPUTERS TO LIFE

Copyright © MANHATTAN

