

CASE/POWER SUPPLY FAN REFERENCE GUIDE

Thank you for your purchase of this MANHATTAN® Case/Power Supply Fan. With an easily installed, high-quality sleeve-bearing design, it helps circulate cool air through the case to dissipate heat away from processors and components to reduce heat damage.



*Shown: Model 703314,
which is representational of
the entire line of sleeve-bearing fans.*

- 3- or 4-pin power connector for easy installation (see Specifications on the back of this reference guide for details)
- Ideal for new systems, upgrades and replacements
- Sleeve bearing delivers quiet, reliable operation
- ISO-certified; meets CE, RU, CSP, WEEE standards
- Mounting screws included
- Lifetime Warranty


MANHATTAN
BRINGING COMPUTERS TO LIFE

MANHATTAN® offers a complete line of PC Components, Peripherals, Cables and Accessories. Ask your local computer dealer for more information or visit us online at **www.manhattan-products.com**

Copyright © MANHATTAN

All products mentioned are trademarks or registered trademarks of their respective owners.

MH-FANSLV-miniQIG-0808-02

SPECIFICATIONS

Model 703314

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.09 A (max.)
- Air flow: 48 cfm (max.)
- Fan speed: 5,000 rpm
- Noise level: 28 dBA (max.)
- Operating temp: -10–70°C
- 40 x 40 x 10 mm
- 14.2 g (0.5 oz.)

Model 703321

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.18 A (max.)
- Air flow: 16 cfm (max.)
- Fan speed: 3,500 rpm
- Noise level: 29 dBA (max.)
- Operating temp: -10–70°C
- 60 x 60 x 20 mm
- 42.5 g (1.5 oz.)

Model 703345

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.18 A (max.)
- Air flow: 27 cfm (max.)
- Fan speed: 2,000 rpm
- Noise level: 25 dBA (max.)
- Operating temp: -10–70°C
- 90 x 90 x 25 mm
- 79.4 g (2.8 oz.)

Model 703352

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.25 A (max.)
- Air flow: 70 cfm (max.)
- Fan speed: 1,800 rpm
- Noise level: 28 dBA (max.)
- Operating temp: -10–70°C
- 120 x 120 x 25 mm
- 122 g (4.3 oz.)

Model 700955

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.15 A (max.)
- Air flow: 31 cfm (max.)
- Fan speed: 2,500 rpm
- Noise level: 29 dBA (max.)
- Operating temp: -10–70°C
- 80 x 80 x 25 mm
- 53 g (1.9 oz.)

Model 700665

- Connector: 4-pin, 3-lead Molex pass-through
- Rated voltage: 12 V DC
- Input current: 0.09 A (max.)
- Air flow: 4.8 cfm (max.)
- Fan speed: 5,000 rpm
- Noise level: 28 dBA (max.)
- Operating temp: -10–70°C
- 40 x 40 x 10 mm
- 34 g (1.2 oz.)

Model 700320

- Connector: 4-pin, 2-lead Molex pass-through
- Rated voltage: 12 V DC
- Input current: 0.15 A (max.)
- Air flow: 31 cfm (max.)
- Fan speed: 2,500 rpm
- Noise level: 25 dBA (max.)
- Operating temp: -10–70°C
- 80 x 80 x 25 mm
- 53 g (1.86 oz.)

Model 700337

- Connector: 4-pin, 2-lead Molex pass-through
- Rated voltage: 12 V DC
- Input current: 0.25 A (max.)
- Air flow: 27 cfm (max.)
- Fan speed: 2,000 rpm
- Noise level: 25 dBA (max.)
- Operating temp: -10–70°C
- 92 x 92 x 25 mm
- 120 g (4.9 oz.)

Model 701655

- Connector: 4-pin, 2-lead Molex pass-through
- Rated voltage: 12 V DC
- Input current: 0.25 A (max.)
- Air flow: 70 cfm (max.)
- Fan speed: 1,800 rpm
- Noise level: 28.5 dBA (max.)
- Operating temp: -10–70°C
- 120 x 120 x 25 mm
- 56 g (2 oz.)