

# CASE/POWER SUPPLY FAN REFERENCE GUIDE

Thank you for your purchase of this MANHATTAN® Case/Power Supply Fan. With an easily installed, high-quality ball-bearing design, it helps circulate cool air through the case to dissipate heat away from processors and components to reduce heat damage.



*Shown: Model 703277,  
which is representational of  
the entire line of ball-bearing fans.*

- 3- or 4-pin power connector for easy installation (see Specifications on the back of this reference guide for details)
- Ideal for new systems, upgrades and replacements
- Ball bearing delivers quiet, reliable operation
- ISO-certified; meets CE, RU, CSP, WEEE standards
- Mounting screws included
- Lifetime Warranty

  
**MANHATTAN**  
BRINGING COMPUTERS TO LIFE

MANHATTAN® offers a complete line of PC Components, Peripherals, Cables and Accessories. Ask your local computer dealer for more information or visit us online at **[www.manhattan-products.com](http://www.manhattan-products.com)**

Copyright © MANHATTAN

All products mentioned are trademarks or registered trademarks of their respective owners.

MH-FANBAL-miniQIG-0808-03

# SPECIFICATIONS

## Model 703277

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.09 A (max.)
- Air flow: 2.29 cfm (max.)
- Fan speed: 4,500 rpm
- Noise level: 24 dBA (max.)
- Operating temp: -10–70°C
- 40 x 40 x 10 mm
- 14.6 g (0.5 oz.)

## Model 703284

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.18 A (max.)
- Air flow: 16 cfm (max.)
- Fan speed: 3,300 rpm
- Noise level: 25 dBA (max.)
- Operating temp: -10–70°C
- 60 x 60 x 20 mm
- 41 g (1.45 oz.)

## Model 703291

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.18 A (max.)
- Air flow: 35 cfm (max.)
- Fan speed: 2,200 rpm
- Noise level: 26 dBA (max.)
- Operating temp: -10–70°C
- 90 x 90 x 25 mm
- 76.5 g (2.7 oz.)

## Model 703307

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.25 A (max.)
- Air flow: 66 cfm (max.)
- Fan speed: 1,800 rpm
- Noise level: 30 dBA (max.)
- Operating temp: -10–70°C
- 120 x 120 x 25 mm
- 122 g (4.3 oz.)

## Model 701747

- Connector: 3-pin
- Rated voltage: 12 V DC
- Input current: 0.15 A (max.)
- Air flow: 31 cfm (max.)
- Fan speed: 2,500 rpm
- Noise level: 30 dBA (max.)
- Operating temp: -10–70°C
- 80 x 80 x 25 mm
- 53 g (1.86 oz.)

## Model 703239

- Connector: 4-pin, 2-lead Molex pass-through
- Rated voltage: 12 V DC
- Input current: 0.09 A (max.)
- Air flow: 2.29 cfm (max.)
- Fan speed: 5,500 rpm
- Noise level: 24.85 dBA (max.)
- Operating temp: -10–70°C
- 40 x 40 x 10 mm
- 20 g (0.7 oz.)

## Model 700863

- Connector: 4-pin, 2-lead Molex pass-through
- Rated voltage: 12 V DC
- Input current: 0.2 A (max.)
- Air flow: 16.56 cfm (max.)
- Fan speed: 3,300 rpm
- Noise level: 25.85 dBA (max.)
- Operating temp: -10–70°C
- 60 x 60 x 20 mm
- 53 g (1.8 oz.)

## Model 700894

- Connector: 4-pin, 2-lead Molex pass-through
- Rated voltage: 12 V DC
- Input current: 0.15 A (max.)
- Air flow: 31 cfm (max.)
- Fan speed: 2,500 rpm
- Noise level: 30 dBA (max.)
- Operating temp: -10–70°C
- 80 x 80 x 25 mm
- 53 g (1.9 oz.)

## Model 700887

- Connector: 4-pin, 2-lead Molex pass-through
- Rated voltage: 12 V DC
- Input current: 0.2 A (max.)
- Air flow: 16.86 cfm (max.)
- Fan speed: 2,200 rpm
- Noise level: 26.4 dBA (max.)
- Operating temp: -10–70°C
- 92 x 92 x 25 mm
- 53 g (1.8 oz.)

## 700924

- Connector: 4-pin, 2-lead Molex pass-through
- Rated voltage: 12 V DC
- Input current: 0.23 A (max.)
- Air flow: 66.3 cfm (max.)
- Fan speed: 1,800 rpm
- Noise level: 30.06 dBA (max.)
- Operating temp: -10–70°C
- 120 x 120 x 25 mm
- 130 g (4.5 oz.)