



DisplayPort to Mini DisplayPort Adapter

DisplayPort Male to Mini DisplayPort Female, 15 cm (6 in.), Black

Part No.: [353403](#)

EAN-13: 0766623353403 | UPC: 766623353403

Easily connects a DisplayPort source or display with a Mini DisplayPort cable.

The Manhattan DisplayPort to Mini DisplayPort Adapter delivers both high-definition digital audio and video signals between desktop or notebook computers and an output device. The 20-pin connector is small and compact but offers 14.8 Gbps bandwidth, Deep Color and 24-bit, 8-channel uncompressed audio capability. It's ideal for use with DisplayPort-equipped computers, flat-panel displays, slim-profile devices and many consumer electronics including Blu-ray players and game consoles. Full foil and braided shielding, molded boots with strain relief, protective PVC jackets and gold-plated connections ensure that the Manhattan DisplayPort to Mini DisplayPort Adapter provides maximum conductivity and clear, crisp signal transmissions with reduced EMI interference and distortion.

Features:

- Easily connect a DisplayPort cable to a Mini DisplayPort device or monitor
- DisplayPort 20-pin male to Mini DisplayPort 20-pin female with latching connection and strain relief boots
- Delivers high-bandwidth, bi-directional, 14.8 Gbps, digital audio/visual signals from source to display — up to 4Kx2K@60Hz
- 4K, UHD resolution supports video resolution four times 1080p; up to 1080p resolution in 3D and Deep Color
- Dolby and DTS-HD 2/5.1/7.1/8 uncompressed surround sound audio pass-through

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Fully shielded to reduce EMI and other interference sources
- Supports the HDCP and DPCP, content protection standards
- Lifetime Warranty

Specifications:

Standards and Certifications

- UL 20276
- DisplayPort 1.2
- ISO 9002

General

- Bandwidth: 14.8 Gbps at 600 MHz
- Meets or exceeds existing DisplayPort standards
- Length: 15 cm (6 in.)

Connectors

- DisplayPort 20-pin male with latch (1)
- Mini DisplayPort 20-pin female (1)
- Gold plated
- Gold-plated contacts
- ABS boots, built-in PVC strain relief

Cable

- 32 AWG
- Shielding: aluminum and Mylar braid
- Withstanding voltage: 300 VDC
- Insulation resistance: 5 MOhm
- Contact resistance: 10 Ohms
- Current rating: 0.5 A DC
- Conductive resistance: 5 Ohms
- Thermal plastic casing

Operating Environment

- Operation Temperature: 0 - 50°C (32 - 122°F)
- Storage Temperature: -25 - 85°C (-13 - 185°F)
- Humidity (noncondensing): 0 - 96%

Package Contents

- DisplayPort to Mini DisplayPort Adapter

