



19" Server Cabinet, 36U, 1000 (D) x 600 (W) x 1766 (H) mm, Gray

IP20-rated housing, Assembled, Steel Panels, Maximum Static Load 1500 kg, Reversible Front Door

Part No.: **713337**

EAN-13: 0766623713337 | UPC: 766623713337

The Intellinet Network Solutions server cabinets offer you a flexible and comprehensive solution for your server installations. Our service starts with the shipping condition – get the completely assembled cabinet delivered or save space and money with the flatpack version. In terms of housing, you have numerous 19" options, all with an installation depth of 1000 mm: With heights from 26 to 42 units in black (RAL9005) or gray (RAL7035), we offer you a solution for every need. The removable side panels and the lockable doors make cabling and component exchange particularly easy. Perforation on front and back provide excellent airflow. In material and workmanship, we provide top quality. Part of that is a cold-rolled steel frame, zinc-plated 19" mounting rails and antistatic powder coating on all panels.

Features:

- Ideal for all 19" rackmount applications
- Maximum static load of 1500 kg
- Perforated door and ventilation slots provide excellent airflow
- Zinc-plated 19 in. mounting rails
- Antistatic powder coating on all panels

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Panels with up to 2 mm steel thickness
- Reversible front door
- IP20-rated housing
- Easily removable side and rear panels
- Multi-point door lock
- Two apertures allow cable inlet from top or bottom
- Ships fully assembled
- Three-Year Warranty

Specifications:

General

- 19 in.
- Height: 36U
- Color: Gray RAL7035
- Certifications: RoHS, UL, Gost-R
- Protection rating: IP20

Dimensions

- Internal: 950 (D) x 503 (W) x 1162 (H) [mm] / 37.4 (L) x 27.68 (W) x 63.27 (H) [in.]
- External: 1000 (D) x 600 (W) x 1607 (H) [mm] / 39.37 (L) x 23.62 (W) x 69.53 (H) [in.]
- Adjustable Depth Range: 123 to 773 mm / 4.84 to 30.43 in.

Package Contents:

- 4 depth-adjustable mounting rails
- 4 adjustable supporting feet
- Installation hardware



