



Hi-Speed USB 2.0 Device Cable

A Male / Mini B Male, 0.3 m (1 ft.), Translucent Silver

Model
322652

Quality connections for superior performance.

MANHATTAN® Hi-Speed USB 2.0 Device Cables easily connect computers and USB-powered peripherals. Ideal for use with printers, scanners, external enclosures and an expanding assortment of digital devices, MANHATTAN Hi-Speed USB Device Cables are engineered and constructed of quality materials that support data transfer rates up to 480 Mbps to deliver dependable, error-free transmissions. Full foil and braided shielding, gold-plated contacts and molded boots with strain relief help ensure maximum conductivity for the fast connection of USB-enabled devices with reduced EMI interference and minimal data degradation.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.



Technical Drawing

REV.	DESCRIPTION	ENG.	APPROVAL

USB(A)
Transparent MOLDING

MINI B5P
Transparent MOLDING

NOTE:

- CABLE:UL2725,USB2.0VER,CABLE,AL+B,28AWG*1P+28AWG*2C,OD=3.5mm,Transparent COLOR,PVC JACKET,(CCA BRAID)
- LENGTH:1FT
- CONNECTOR:USB(A)*1 PCS,MINI B5P*1 PCS
- MOLD:Transparent MOLDING
- CONTACTS:

USB(A)	1	2	3	4	64
MINI B5P	1	2	3	5	64
	RED	WHITE	GREEN	BLACK	SHIELD
		+28	+28		
		PAIR			

WHITE/GREEN PAIR...28AWG, RED/BLACK...28AWG

- OPEN/SHORT TEST: 100% TEST.
INSULATION:5M.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF MANHATTAN AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF MANHATTAN.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCES:±1°

TOLERANCES (MM)		TOLERANCES (IN)	
0	+0.10°	0	+0.004
0.1	+0.05°	0.1	+0.002
0.25	+0.03°	0.25	+0.001
0.508	+0.02°	0.508	+0.001

MANHATTAN		TITLE:	APPD:
		CUSTOMER:	Check: XIE
		CUSTOMER P.N.:	Drawn: WJE
		DATE:	Scale: 1:1
		DWG. NO.:	Sheet 1 of 1

Features

- USB type-A male to USB mini B male
- Connects a USB device to a USB hub or computer
- Speeds of up to 480 Mbps
- Hi-Speed USB for ultra-fast data transfer rates with zero data degradation
- Fully shielded to help reduce EMI and other interference sources
- Lifetime Warranty

Specifications

STANDARDS AND CERTIFICATIONS

- UL
- USB 2.0

CONTACTS

- (1) type-A male
- (1) mini B male
- Molded PVC boot
- 28 AWG connectors

CABLE

- Shielded
- Length: 0.3 m (1 ft.)
- Withstanding voltage: 300 V DC
10 ms
- Insulation resistance: 5 MOhms
- Contact resistance: 10 Ohms
- Thermal plastic casing

PACKAGE CONTENTS

- Hi-Speed USB 2.0 Device Cable

For more information on MANHATTAN products, consult your local dealer or visit www.manhattan-products.com.



Copyright © MANHATTAN

