



## USB to Serial Converter

Connects One Serial Device to a USB Port, Prolific PL-2303 Chip, 1.8 m (6 ft.)

Part No.: [151832](#)

EAN-13: 0766623151832 | UPC: 766623151832

### Easily connect serial devices through a USB port

Most modern computers and laptops don't have RS232 (DB9) ports, making the use of legacy peripherals and high-tech devices which connect with COM ports almost impossible. The Manhattan USB to Serial Converter — with its serial RS232 (DB9) port and Prolific PL-2303 chipset — easily expands a single USB port to connect and support serial modems, barcode scanners, digital cameras, card readers, Ham/Amateur Radios, GPS, CNC machines, telescopes, embroidery machines, fuel injection controllers, PDUs, network switches and other devices.

### Quality Construction and Easy Installation

Gold-plated contacts and rugged construction combine to offer a reliable connection between the computer and serial peripherals for consistent, trouble-free performance. Windows compatibility with plug-and-play installation and hot-swappability help provide seamless use without inconvenient and frustrating device conflicts.

#### Features:

- Quickly converts a USB port to a Serial/RS232/COM/DB9 port
- The customizable and compatible Prolific PL-2303 chipset makes it the ideal solution for many OSs and platforms
- Easily connect most DB9/serial modems, digital cameras, label writers, barcode scanners, palm PCs, GPS, telescopes, CNC machines,

For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

embroidery machines, automotive control systems, digital organizers and much more

- Install as a standard COM/RS-232 port to provide serial connectivity for legacy and high-tech devices
- Chipset FTDI FT232RL configurations are also available at [ManhattanProducts.com](http://ManhattanProducts.com)
- Windows compatible; plug and play; hot-swappable
- Lifetime Warranty

## Specifications:

### Standards and Certifications

- CE
- FCC
- USB 1.0
- USB 1.1
- RoHS
- WEEE

### Connections

- USB port; type-A male
- Serial/COM/RS232/DB9 port; 9-pin male

### General

- Transfer rate: up to 115 kbps
- Bus powered
- Overcurrent protection
- Prolific PL-2303 chipset

### Physical

- 24 AWG cable gauge
- Cable length: 1.8 m (6 ft.)
- Weight: 165 g (5.8 oz.)

### System Requirements

- Windows XP/Vista/7/8/8.1/10 or Linux or Mac 9.x/10.x or above

### Package Contents

- USB to Serial Converter
- Instructions

