



USB to Serial Converter

Connects One Serial Device to a USB Port, Prolific PL-2303RA Chip, 1.8 m (6 ft.), Polybag

Part No.: [151849](#)

EAN-13: 0766623151849 | UPC: 766623151849

Easily connect serial devices through a USB port.

Most modern computers and laptops don't have RS232 (DB9) ports, making the use of legacy peripherals and high-tech devices which connect with COM ports almost impossible. The Manhattan USB to Serial Converter — with its serial RS232 (DB9) port and Prolific PL-2303RA chipset — easily expands a single USB port to connect and support serial modems, barcode scanners, digital cameras, card readers, Ham/Amateur Radios, GPS, CNC machines, telescopes, embroidery machines, fuel injection controllers, PDUs, network switches and other devices.

Quality Construction and Easy Installation

Gold-plated contacts and rugged construction combine to offer a reliable connection between the computer and serial peripherals for consistent, trouble-free performance. Windows compatibility with plug-and-play installation and hot-swappability help provide seamless use without inconvenient and frustrating device conflicts.

Features:

- Quickly converts a USB port to a Serial/RS232/COM/DB9 port
- The customizable and compatible Prolific PL-2303RA chipset makes it the ideal solution for many OSs and platforms
- Easily connect most DB9/serial modems, digital cameras, label writers, barcode scanners, palm PCs, GPS, telescopes, CNC machines, embroidery machines,

automotive control systems, digital organizers and much more

- Install as a standard COM/RS-232 port to provide serial connectivity for legacy and high-tech. devices
- Chipsets PL-2303HXD and FTDI FT232RL configurations are also available at ManhattanProducts.com
- Windows compatible; plug and play; hot-swappable
- Lifetime Warranty

Specifications:

Standards and Certifications

- CE
- FCC
- USB 1.0
- USB 1.1
- RoHS
- WEEE

Connections

- USB port; type-A male
- Serial/COM/RS232/DB9 port; 9-pin male

General

- Transfer rate: up to 115 kbps
- Bus powered
- Overcurrent protection
- Prolific PL-2303RA chipset

Physical

- 24 AWG cable gauge
- Cable length: 1.8 m (6 ft.)
- Weight: 165 g (5.8 oz.)

System Requirements

- Windows XP/Vista/7/8/8.1/10 or Linux or Mac 9.x/10.x or above

Package Contents

- USB to Serial Converter
- Instructions and driver CD

