


Cable Profile View



1, Patchcord Length (m)

Length L	Tolerance T	Part No	Packing Bag Size
L = 2.0m	±0.10m	515795	180x280mm
L = 5.0m	±0.10m	510356	180x280mm
L = 10.0m	±0.10m	515801	180x280mm

2, Connector Test Specifications

Parameters	Specifications
Insertion Loss	≤0.30dB
Return Loss	≥35.0dB
Durability(1000Mating)	0.2dB Max.Increase
Operating Temperature	-40℃~75℃
Storage Temperature	-40℃~85℃

ITEM	DESCRIPTION	Q'TY
1	SC Dust Cap (Clear)	4
2	SC/UPC Connector MM Duplex 3.0mm (Beige)	2
3	SC Duplex Clip (Beige)	2
4	SC 3.0 Boot (Red)	2
5	SC 3.0 Boot (Black)	2
6	ST 3.0mm Boot (Red)	2
7	ST 3.0mm Boot (Black)	2
8	ST/UPC Duplex metal Connector MM Ø3.0mm	2
9	ST Dust Cap (Clear)	2
10	MM Duplex 62.5/125 3.0mm LSZH Cable(Orange)	Xm



DRAWN BY	LW	SPEC.	SC/UPC-ST/UPC MM-Duplex 62.5/125 3.0mm Patchcord L=Xm, LSZH Orange Jacket	A
CHECK BY	ZH	CUSTOMER	SHEET /P	SCALE NONE UNIT: mm
APPD. BY	ZH	DWG. NO.	DATE 2015-04-07	VIEW