



8-Port Rackmount LCD Console KVM Switch

17-Inch LCD Panel, PS/2 or USB, 1U, connection cables included

Part No.: **506540**

EAN-13: 0766623506540 | UPC: 766623506540

Convenient access and control.

The INTELLINET NETWORK SOLUTIONS Model 506540 8-Port Rackmount Console KVM Switch allows easy and convenient access to eight servers while allowing full control from a single device.

Easy and Convenient

With the industry-standard 19" 1U-height rack drawer, the Rackmount Console KVM Switch can be easily pulled out and accessed in the extended position, and the display can be folded down, locked and secured when stored.

Full Functionality

With superior KVM functionality, you can manage and control eight PS/2 or USB computers from this single device.

Features:

- Integrated LCD console, keyboard, mouse, and KVM switch module for rack-mount installation
- Manage/control 8 PS/2 or USB computers from one keyboard, monitor and mouse
- Includes eight 1.8 m (6 ft.) connection cables for PS/2 or USB computers
- Standard 19 inch 1U rack drawer
- Gain complete control with easy-to-use OSD interface
- Flip-open 17 inch LCD panel (2048 x 1536 highest resolution; 1280 x

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

1024 optimal resolution)

- Adjustable - for rack cabinets with depths from 600 mm to 1200 mm (23.6 to 47 in.)
- Full 105 key, low-profile, sturdy keyboard included
- Ergonomic hand rest design
- Ultra sturdy rear bracket and extension design
- Modularized KVM switch design
- OSD control and adjustment
- Auto-scan automatically selects computers sequentially
- Supports both PS/2 and USB mouse
- Operating system independent, transparent to all applications
- Plug and Play system configuration
- Keyboard and mouse can be hot plugged at any time
- Three-Year Warranty

Specifications:

Standards

- PS/2
- USB
- Compatible with Windows, MAC and Unix

General

- PC connections: 8
- Cable type: PS/2 or USB combo cable
- Console connections: 1
- PC port connectors:
 - Keyboard + mouse + monitor: HD15 x 8
- Console port connectors:
 - Keyboard: PS/2 & USB
 - Mouse: PS/2 & USB
 - Monitor: HD15 female
- Computer selection:
 - Via buttons
 - Via hotkeys
- OSD: yes
- Video resolution: max. 2048 x 1536
- Video bandwidth: 300 MHz
- FCC Class B, CE, RoHS

Power

- Power input (AC): approx. 100 - 240 V
- MTBF: 60,000 hours

LCD Panel

- Active display area: 337.9 x 270.3 (mm)
- Pixel pitch: 0.264 (H) x 0.264 (W)

- Resolution: 2048 x 1536 @ 60 Hz; 1280 x 1024 @ 75 Hz
- Brightness: 250 (Typ)
- Contrast ratio: 400:1 (Typ)
- Display color: 16.2 M colors
- User control: OSD control (auto saving)
- Backlight unit: 4-CCFL type
- MTBF: 50,000 hours

Environmental

- KVM module dimensions: 42 (H) x 443 (W) x 685 (D) mm (1.6 x 17.4 x 27 in.)
- Weight: 20.6 kg (45.4 lbs.)
- Operating temperature: 0 – 50°C
- Storage temperature: -20 – 60°C (-4 – 140°F)

Package Contents

- 8-Port Rackmount Console KVM Switch
- Rear bracket and extension kit
- KVM switch module
- Power adapter
- Eight 1.8 m (6 ft.) PS/2 and USB combo cables
- KVM Switch Module user manual



For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

