



## **iLynk USB Cable with Lightning Connector**

**USB 2.0, Type-A Male to 8-Pin Male, 15 cm (6 in.), Blue**

Part No.: [394437](#)

EAN-13: 0766623394437 | UPC: 766623394437

---

Quality connections for superior performance.

Manhattan iLynk Lightning Cables easily connect 8-pin-connector iPods, iPads and iPhones to USB-equipped computers, hubs, docks and more. Ideal for synchronization and charging, Manhattan iLynk Lightning Cables are constructed of quality materials that support dependable, error-free data-transfer rates up to 480 Mbps. A durable, flexible, PVC-jacketed, super-short cable is perfect for connecting Apple mobile devices to battery power banks without extra, ungainly cable length to hide or hold.

### **Features:**

- USB Type-A male to 8-pin male
- Supports speeds up to 480 Mbps
- Connects an iPod, iPad or iPhone to a USB port
- Ideal replacement or spare cable for synchronization and charging
- Lifetime Warranty

### **Specifications:**

#### Standards and Certifications

- UL 2725
- MFi
- USB 2.0

#### Connectors

- One Type-A male
- One 8-pin iPod/iPad/iPhone male
- Nickel plated

For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Molded PVC boot with strain relief

#### Cable

- 30 AWG cable
- Shielded
- Current rating: 0.5 ADC
- Withstanding voltage: 300 VDC
- Insulation resistance: 10 MOhm
- Conductive resistance: 5 Ohm
- Thermal plastic casing

#### Physical

- Length: 15 cm (6 in.)
- Weight: 11 g (0.4 oz.)

#### Operating Environment

- Operation temperature: 0 - 50°C (32 - 122°F)
- Storage temperature: -20 - 50°C (-4 - 122°F)
- Humidity (noncondensing): 0 - 96%

#### Package Contents

- iLynk USB Cable with Lightning Connector



