



56 K Modem PCI Card

Data / Fax / Voice Modem

Part No.: **153577**

Easily connect with better speed and convenience.

The MANHATTAN 56 K Modem PCI Card with V.92 technology helps create a high-speed connection solution between a desktop computer and standard telephone line to send/receive email and faxes, search the Web and accept incoming telephone calls while online. By enabling faster downstream speeds with reliable and steady connections, the MANHATTAN 56 k Modem PCI Card helps to quickly upload and download digital images, email attachments, audio and video and other large files while improving views of graphics-intensive web pages.

Features:

- Supports data transmission up to V.92 (56 kbps data download rate & 33.6 kbps data transmit rate)
- Supports fax transmission up to V.29 (14.4 kbps transmission rate)
- Supports voice transmission including software speakerphone
- Hayes compatible for instant installation
- Lifetime Warranty

Specifications:

Standards and Certifications

- FCC
- CE
- RoHS
- WEEE

General

- Full function speakerphone (through sound card), Digital Telephone Answering Machine (TAM) and video conferencing V.80 and H.324 support
- Operating modes: Auto dial/answer, full-duplex or half duplex in data mode, half-duplex in fax mode and dial-up operation
- Interface: 32-bit PCI
- Data compatibility: ITU-T V.92, V.90, V.34, V.32, V.22 bis and V.21 Bell 212A and 103
- Data speed: 56000(downstream), 33600, 31200, 28800, 26400, 21600, 19200, 16800, 14400, 12000, 9600, 7200, 4800, 2400, 1200 and 300 bps
- Fax compatibility: ITU-T: V.29, V.27ter and V.21 ch2; Class 1; Fax Group 3

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Fax speed: 14400, 12000, 9600, 7200, 4800, 2400 bps
- Error correction: MNP 2-4, ITU-T V.42
- Data compression: MNP 5, ITU-T V.44 bis, V.42 bis
- DTE speed: 115,200 bps
- Data format: Serial, Binary, asynchronous, 7 or 8 data bits, odd, even or no parity, one or two stop, totally 10bits length
- Dial Type: Tone and pulse
- Command set: AT command set
- Flow control: XON/XOFF, CTS/RTS

System Requirements

- Sound card required
- Windows 2000/XP/Vista/7 and DOS/Linux compatible

Dimensions

- 120 x 40 mm (4.7 x 1.57 in.)

Package Contents

- 56 K Modem PCI Card
- Telephone (RJ-11) cable included, 1.5 m (5 ft.)
- Software CD and User Manual



