



3-in-1 4K Mini DisplayPort Adapter

Mini DisplayPort Male to HDMI/DVI-I/VGA Female, Active, Black

Part No.: [207720](#)

EAN-13: 0766623207720 | UPC: 766623207720

Easily connect a Mini DisplayPort source with an HDMI, DVI or VGA display

The Manhattan 3-in-1 4K Mini DisplayPort Adapter establishes a fast, simple and convenient link between Mini DisplayPort-equipped sources and existing 4K HDMI and 1080p DVI and VGA displays. The adapter is easy and quick to install and requires no complicated configuration or setup. It offers a passive, compact and integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Features:

- 3-in-1 adapter converts a Mini DisplayPort signal to a 4K@30Hz HDMI or 1080p@60Hz DVI or VGA signal (no simultaneous output)
- Delivers a high-quality digital video signal — ideal for using a Mini DP source with an HDMI, DVI or VGA display
- Supports Deep Color, high-bandwidth 3 Gbps applications and resolutions at 1080p@60Hz (up to 1920 x 1200) for VGA and DVI or 4K@30Hz (3840 x 2160) for HDMI
- Allows monitor, TV or display to be configured in Extended or Mirrored modes
- HDMI configuration supports high definition video resolution up to 4K@30Hz (3840 x 2160p) and uncompressed digital 5.1 audio
- DVI configuration supports high definition video resolution up to 1080p@60Hz (1920 x 1080p); DVI does not support audio
- VGA configuration supports high-definition video resolution up to 1080p@60Hz (1920 x 1080p); VGA does not support audio
- Compatible with DVI-I and DVI-D interfaces

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Integrated design simplifies connections and eliminates cable tangles and clutter
- Three-year warranty

Specifications:

Standards and Certifications

- UL 20276
- DisplayPort v1.2
- FCC
- CE

Connections

- Mini DisplayPort 20-pin male
- HDMI 19-pin female, passive
- DVI-I 24+5-pin female, passive
- VGA/HD15 15-pin female, active
- Nickel-plated contacts
- Molded PVC and ABS Shell

General

- 8-bit and 10-bit Deep Color support
- 3 Gbps bandwidth
- Maximum single link resolution
3840 x 2160 (4K@30Hz) for HDMI
1920 x 1200 (1080p@60Hz) for DVI and VGA
- One-lane, one-direction, four-line connection support
- Active

Video Resolutions

- VGA: 640 x 480, 800 x 600, 1024 x 768, 1920 x 1200
- DTV/HDTV/UHDTV: 480i/480p/576i/576p/720p/1080i/1080p/4K@30Hz

Physical

- Cable length: 25 cm (10 inches)
- Housing: 7.5 x 4 x 1.8 cm (2.95 x 1.8 x 0.7 in.)
- Weight: 48 g (1.7 oz.)
- Housing: plastic

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 - 80%

System Requirements

- Windows XP/Vista/7/8.1/10, Linux or Mac 9.x/10.x or above

Package Contents

- 3-in-1 4K Mini DisplayPort Adapter
- Quick Instruction Guide

