



USB-C to HDMI Converter

USB-C Male to HDMI Female, White

Part No.: [152921](#)

EAN-13: 0766623152921 | UPC: 766623152921

Easily connect a USB type-C source with an HDMI display.

The Manhattan SuperSpeed+ USB-C to HDMI Converter establishes a fast, simple and convenient link between a newer USB type-C-equipped media source (computer, tablet, etc.) and an existing HDMI display (monitor, projector, etc.). The Manhattan SuperSpeed+ USB-C to HDMI Converter is easy and quick to install — no complicated configuration or setup required. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly. Extend the service life of your equipment, and fully realize the investment and value of your HDMI displays, projectors and peripherals with a Manhattan SuperSpeed+ USB-C to HDMI Converter.

Features:

- Converts USB video and audio to an HDMI signal
- Delivers Ultra-High-Definition (UHD) video to an HDMI monitor, projector or other display device
- Supports video resolutions up to 3840x2160p@30Hz
- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Plug and Play; requires no external power supply
- Compatible with all USB type-C supported desktops, notebooks and tablets including Apple MacBook®, Chromebook Pixel™ and more
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime warranty

Specifications:

Standards and Certifications

- USB 3.1
- HDMI
- HDCP 1.4
- CE
- FCC
- RoHS2
- WEEE

Connections

- USB type-C, 24-pin, male
- HDMI, 19-pin, female
- Shielded

Video Resolutions

- 640x480, 800x600, 1024x768, 1920x1200, 3840x2160p@30Hz

Physical

- 32-AWG cable gauge
- Mylar and aluminum shielding
- Thermal plastic casing
- Length: 8 cm (3 in.)
- Weight: 31 g (1.1 oz.)
- Shielded
- Housing: ABS plastic

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 65°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- Windows XP/Vista/7/8.1/10 or Linux or Mac 9.x/10.x or above

Package Contents

- SuperSpeed+ USB-C to HDMI Converter
- Quick Instruction Guide

