



USB-C HDMI Docking Converter

USB 3.2 Type-C Male to HDMI, USB-A and USB-C Females, Multiport Converter, White

Part No.: [152945](#)

EAN-13: 0766623152945 | UPC: 766623152945

Easily connect a USB type-C device with an HDMI display and USB peripherals

The Manhattan USB Type-C HDMI Docking Converter establishes a fast, simple and convenient link between newer USB type-C equipped media sources (computers, tablets, etc.) and existing HDMI displays (monitors, projectors, etc.), in either mirror- or extended-display mode. Create a mini-workstation by adding any USB 3.0 peripheral such as a mouse, keyboard, hub, external memory device and more with the integrated USB 3.0 port. Charge a device through the type-C charging port. The Manhattan USB Type-C HDMI Docking Converter is easy and quick to install. No complicated configuration or setup is required to enhance the functionality of your type-C device. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and work spaces neat and orderly.

Features:

- Multi-function docking converter connects a USB Type-C port to an HDMI display, USB 3.2 Gen 1, SuperSpeed (5 Gbps) Type-A port and Type-C charging port
- Delivers Ultra-High-Definition (UHD) video and audio to an HDMI monitor, projector or other display device
- Mirror or Extended display modes support video resolutions up to 1080p@60Hz or 3840x2160p@30Hz (4K, Full UHD)
- Provides a standard USB 3.0 type-A port to connect mice, keyboards or portable memory devices (and more) or to charge and sync a portable electronic device
- USB-A port supports SuperSpeed (5 Gbps) data transmission and charging up to 7.5 W (5 V / 1.5 A); BC1.2 compliant
- USB-C port only supports charging — up to 60 W (20 V @ 3 A)

- USB-C plug supports 5 Gbps data transmission
- Supports USB Power Delivery (PD) function up to 60 W; requires an external PD charger – available from Manhattan
- Compatible with all USB type-C supported desktops, notebooks and tablets including Apple MacBook®, Chromebook Pixel™ and more
- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Plug and Play
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime warranty

Specifications:

Standards and Certifications

- USB 3.1
- HDMI
- HDCP 1.4
- CE
- FCC
- RoHS2
- WEEE

General

- Bus powered, up to 60 watts
- Overcurrent protection

Connections

- USB type-C, 24-pin, male
- HDMI, 19-pin, female
- USB type-C, 10-pin, female; power only
- USB type-A, 4-pin, female

Video Resolutions

- 640x480, 800x600, 1024x768, 1920x1200, 3840x2160p@30Hz (4K)

Physical

- 24-AWG cable gauge
- Mylar and aluminum shielding
- Withstanding voltage: 300 VDC
- Insulation resistance: 10 MOhm
- Conductive resistance: 5 Ohm
- Thermal plastic casing
- Length: 8 cm (3 in.)
- Weight: 31 g (1.1 oz.)
- Shielded
- Housing: ABS plastic

Operating Environment

- Operation Temperature: -10 – 60°C (14 – 140°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 5 – 90%

System Requirements

- Windows XP/Vista/7/8.1/10 or Linux or Mac 9.x/10.x or above

Package Contents

- SuperSpeed USB-C HDMI Docking Converter
- Quick Instruction Guide

