



Power Delivery Wall Charger - 60 W

USB-C Power Delivery Port (up to 60 W), USB-A Charging Port (up to 2.4 A), White

Part No.: [180221](#)

EAN-13: 0766623180221 | UPC: 766623180221

Power up your devices with a portable, powerful Power-Delivery-capable charger.

Enjoy complete charging power with the Manhattan Power Delivery Wall Charger - 60 W. This wall charger uses Power Delivery (PD) technology to power up any device with a USB-C charging port, from laptops to mobile phones, and the additional USB-A port can quickly charge any handheld device or tablet. The perfect companion for travelers with its stylish, compact and ultra-modern design, the Manhattan Power Delivery Wall Charger - 60 W also intelligently protects itself and your devices with its short-circuit-, overvoltage-, overcurrent- and overtemperature-protection functions.

Features:

- Two-device charging solution with USB-C Power Delivery (PD 3.0) and USB-A charging ports
- Charges two different devices simultaneously with ideal potential energy
- USB-C PD port delivering up to 60 W to charge a notebook, laptop, Ultrabook, tablet or other USB-C powered device

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- USB-A port delivering up to 5 V / 2.4 A to quickly charge a portable device
- Overload, overcurrent and overheat protection
- Compact, portable and stylish design for easy travel
- Three-year warranty

Specifications:

Standards and Certifications

- USB 2.0
- PD 3.0
- FCC
- UL
- CE
- RoHS
- WEEE

Ports

- One USB-C with Power Delivery (PD 3.0)
- One USB-A

General

- AC input: 100 – 240 V; 50 – 60 Hz
- USB-C output: 5 – 20 V; maximum 3 A; 60 W
- Voltage/current settings (maximum):
 - USB-C:
 - 5 V / 3 A
 - 9 V / 3 A
 - 12 V / 3 A
 - 15 V / 3 A
 - 19 V / 3 A
 - 20 V / 3 A
 - USB-A:
 - 5 V / 2.4 A

Input Characteristics

- AC rated voltage: 100 – 240 V
- Frequency range: 50 – 60 Hz (± 1 Hz)
- Current: ≤ 1 A at 100 VAC 60 HZ

Output Characteristics

- Rated voltage: 5 / 9 / 12 / 15 / 19 / 20 V
- Current: 3 A maximum (at constant voltage mode)
- Rated power: 60 watts maximum
- Overshoot voltage: $\leq 5\%$

Protection Characteristics

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Short circuit (SCP) with auto-recovery mode
- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) — current limit: 150% (max)
- Overtemperature (OTP)

Physical

- Dimensions: 7 x 7 x 3 cm (2.76 x 2.76 x 1.18 in)
- Weight: 0.16 kg (4.9 oz.)
- Housing: plastic

Operating Environment

- Operation Temperature: 0 – 30°C (32 – 86°F)
- Storage Temperature: -20 – 65°C (-4 – 149°F)
- Humidity (noncondensing): 10 – 90%

Package Contents

- Power Delivery Wall Charger - 60 W
- Quick Instruction Guide



