



# Cat6 Bulk Cable, Stranded, 24 AWG

UTP, 305 m (1,000 ft.), CM Rated, Plastic Reel, Gray

Part No.: 334143

EAN-13: 0766623334143 | UPC: 766623334143

---

For Data, Voice and Video

The INTELLINET NETWORK SOLUTIONS Cat 6 Bulk Cable networks the infrastructure that enables

high speed transmission of data, voice and video applications - up to 250 Mhz.

The Cat 6 Bulk Cable meets EIA/TIA standards, and is Flame Retardant Rated.

## Features

- Flame Retardant Rating: CM In-wall rated; permitted in 1-2 family residential riser applications, or in riser with raceway/fireproof shaft; not permitted in plenums
- Standards Tested: Meets or exceeds current CAT5e proposed standards
- Length Usage Log on Box: Track remaining cable available for next job

## Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all INTELLINET NETWORK

SOLUTIONS products. All items carry a full Lifetime Warranty —

the strongest quality commitment anyone can make.

## Features:

- Unshielded Twisted Pair
- Can be used in riser with raceway/fireproof shaft
- Standards Tested
- Meets or exceeds current CAT6 proposed standards
- Length Usage Log on Box
- Track remaining cable available for next job
- Lifetime Warranty

## Specifications:

### General

- Gray colored
- Unshielded Twisted 4-Pair
- 24 AWG
- Stranded Core
- PVC Jacket
- Meets or exceeds Cat 6 specifications
- Rated to 250MHz
- Ideal for carrying data, audio, and video
- Flame Retardant Rating: CM

In-wall rated; permitted in 1-2 family residential riser applications, or in riser with raceway/fireproof shaft; not permitted in plenums

- UL Approved

### Technical Specifications

- TIA Cat6 Channel Test 250 MHz:

- Return Loss (db) = 17.32
- Attenuation (db/100) = 33.04
- Near-End Crosstalk (db) = 38.3
- Power Sum-NEXT (db) = 36.3
- Equal Level-FEXT (db) = 19.8
- Power Sum-ELFEXT (db) = 16.8

