



Gigabit Ultra PoE Injector

One 95 W Port, (PoE++ / 4PPoE) Compliant, Plastic Housing

Part No.: 561495

EAN-13: 0766623561495 | UPC: 766623561495

Inject 95 Watts of Power Into Your Internet of Things (IoT) or PoE++ Network!

IEEE 802.3bt Compliant

The Intellinet Network Solutions Gigabit Ultra PoE Injector provides up to 95 W using all four pairs of twisted-pair network cabling to support IoT applications such as lighting, sensors and building automation. Nurse call systems require 30 to 50 watts of power. Point-of-sale card readers & printers need up to 60 watts. Lighting fixtures and controllers require 40 to 50 watts. Some motorized IP cameras need more than 70 watts. The IEEE 802.3bt Ultra PoE standard is an excellent solution for bringing power to these critical systems. As many new IEEE 802.3bt powered devices enter the market, you'll be ready for them with an Intellinet Network Solutions Gigabit Ultra PoE Injector.

Full Compatibility with Existing IEEE 802.3af/at Power over Ethernet devices

The Intellinet Network Solutions Gigabit Ultra PoE Injector helps you connect your IEEE 802.3af/at-compliant products to a non-PoE LAN switch port. The injector can be used to connect a wireless access point, IP phone, network camera or any IEEE 802.3af/at-powered device (PD) to a switch.

Reduced Wiring Costs

It's no longer necessary to run AC power lines for your wireless access point, network camera or IP phone. Simply connect the PoE++ Injector to the LAN switch port, and use the existing network cabling to deliver DC power as well as

transfer data.

Protected Equipment

Once DC power is connected to your networked equipment through the network cabling, this Intellinet Network Solutions PoE++ Injector ensures that your products are protected from power problems like short circuits (short GRND), current overloads and high voltages.

Features:

- Save time and money by delivering data and power via existing network cables
- Total PoE power budget of 95 watts
- Compatible with IEEE 802.3bt (Ultra-PoE), IEEE 802.3at and IEEE 802.3af
- Short-circuit, overload and high-voltage protection
- Supports all IEEE 802.3bt-, IEEE 802.3at- and IEEE 802.3af-compliant PoE devices (Wireless LAN access points and bridges, VoIP [Voice over Internet Protocol] telephones, IP surveillance cameras)
- Distance support: up to 100 m (328 ft.)
- Internal power supply
- Fanless design ideal for silent operation
- Wall-mounting option
- Three-year warranty

Specifications:

Standards

- IEEE 802.3af (Power over Ethernet)
- IEEE 802.3at (High-Power PoE+ Power over Ethernet)
- IEEE 802.3bt (Ultra PoE++/4PPoE Power over Ethernet)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3ab (Gigabit Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)

General

- Media support:
 - 10Base-T Cat5 UTP/STP RJ45, 8 pin
 - 100Base-TX Cat5 UTP/STP RJ45, 8 pin
 - 1000Base-T Cat5e UTP/STP RJ45, 8 pin
- Ports:
 - One RJ45 10/100/1000 Mbps port
 - One RJ45 10/100/1000 Mbps data and power output port
- Protection functions:

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Short-circuit protection
- Over-current protection
- Over-voltage protection
- PoE Pinout
 - Pin 1: DC (-)
 - Pin 2: DC (-)
 - Pin 3: DC (+)
 - Pin 4: DC (+)
 - Pin 5: DC (+)
 - Pin 6: DC (+)
 - Pin 7: DC (-)
 - Pin 8: DC (-)
- Certifications: CE, RoHS, FCC Class A

LED

- Power, Data and PoE LEDs

Power

- Input: 100 – 240 V AC, 50 – 60 Hz

Environmental

- Plastic housing
- Dimensions: 190 (L) x 100 (W) x 40 (H) [mm] 7.48 (L) x 3.94 (W) x 1.57 (H) [in]
- Weight: 0.502 kg (1.11 lbs.)
- Operating temperature: 0 – 40°C (32 – 104°F)
- Operating humidity: 10 – 90% RH, non-condensing
- Storage temperature: -40 – 70°C (-40 – 158°F)

Package Contents

- Gigabit Ultra PoE Injector
- Power cable
- Instructions



For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

