



SuperSpeed USB-C to Dual HDMI Multiport Adapter

USB 3.2 Gen 1 Type-C Male to Two HDMI (up to 4K@30Hz) Females, Two SuperSpeed USB-A Ports, USB-C Power Delivery Port and Gigabit RJ45 Port; Aluminum, Black

Part No.: [152747](#)

EAN-13: 0766623152747 | UPC: 766623152747

An all-in-one USB-C to Dual HDMI Multiport Adapter for reliable connections to your devices

The Manhattan USB-C to Dual HDMI Multiport Adapter turns your limited USB-C device into more complete and accessible hardware. It's a comprehensive connectivity solution that helps you do more with the devices you already have to increase productivity nearly anywhere you are. This multiport adapter helps you expand your workspace or share what you're working on with included dual HDMI ports that connect to your existing HDMI displays (or monitor, projector, etc.; when both ports are used, one display offers 4K resolution and the other offers 1080p@60Hz resolution). You can add up to two peripherals, such as a mouse, keyboard, hub, external memory device and more with its two SuperSpeed USB-A ports. If you need a wired connection to a network, it offers gigabit speeds at its built-in Ethernet port. This adapter is a perfect companion to ultrabooks and MacBooks[®] that offer the USB-C connector since it expands your access to the devices you need to use is easy over one USB-C port.

Superior, easy connections to Ethernet, your HDMI display, and USB peripherals

The Manhattan USB-C to Dual HDMI Multiport Adapter is easy and quick to install. This adapter enhances the functionality of your type-C device right when you connect it — there are no settings to configure or additional steps to get your devices working with this adapter. Its design gives you a compact,

complete solution that eliminates unnecessary cables, tangles and clutter to keep your workspace neat and tidy.

USB-C Power Delivery

The included USB-C Power Delivery port can give up to 60 W (20 V / 3 A) of power to the devices you connect to this Hub and the upstream device the Hub connects to. Simply plug in the upstream device's power adapter and cable. The Power Delivery function also provides faster charging than standard chargers since it determines the power needs of compatible devices and supplies it at the quickest and safest rate.

Multiport Adapter that's made to go where you go

Sturdy aluminum housing makes this multiport adapter the perfect travel companion. Simply slip it into your backpack or computer bag with your main device, and you always have a way to connect to the available compatible devices and display you use to get work done.

Features:

- Durable, portable and powerful USB-C hub that connects you to the network, your displays and multiple USB devices
- Two HDMI ports supporting up to UHD 4K resolution*, two USB 3.2 Gen 1 type-A ports, USB-C Power Delivery (PD) port up to 60 W (20 V / 3 A) and a 10/100/1000 Mbps Ethernet port
- Supports extended mode on Mac OS 10.8 or above
- Supports up to 4K@30Hz resolution in Mirror or Extended mode*
- Up to 5 Gbps data transfer speeds on USB ports following USB 3.2 Gen 1 specification
- Gigabit speeds (10/100/1000 Mbps) on Ethernet port
- Supports Power Delivery up to 60 W (20 V at 3 A) for all connected devices
- Supports USB Power Delivery (PD) function up to 60 W; requires an external PD charger – available from Manhattan
- Ventilation holes to avoid overheating
- Durable aluminum housing, making it the perfect desktop or travel companion
- Plug and play

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Three-year warranty
- *When both HDMI ports are used simultaneously, one port offers 4K@30Hz resolution and the other offers 1080p@60Hz resolution

Specifications:

Standards and Certifications

- USB 3.2 Gen 1
- HDMI 1.4
- CE
- FCC
- RoHS2
- WEEE

General

- Video Resolutions:
 - 640 x 480
 - 800 x 600
 - 1024 x 768
 - 1920 x 1080 (1080p@60Hz)
 - 1920 x 1200
 - 3840 x 2160p at 30 Hz (4K@30Hz)
- USB-A ports: 5 Gbps
- Gigabit Ethernet port: 10/100/1000 Mbps
- Signal 32-AWG cable gauge
- Bus-powered
- USB-C PD Charging Port: 60 W (20 V at 3 A)
- Mylar and aluminum shielding
- Withstanding voltage: 100 VDC
- Insulation resistance: 5 MOhm
- Conductive resistance: 1 Ohm

Connections

Input:

- One USB-C 24-pin, male

Outputs:

- Two HDMI 19-pin, female
- One 10/100/1000 Mbps RJ45, female
- Two USB-A 4-pin, female
- One USB-C 24-pin, Power Delivery, female

Physical

- Dimensions: 13.5 x 54.5 x 15.25 mm (5.18 x 2.15 x 0.6 in.)
- Cable Length: 30 cm (11.81 in.)
- Weight: 111.5 g (3.93 oz.)
- Housing: aluminum

Operating Environment

- Operation Temperature: 0 – 45°C (32 – 113°F)
- Storage Temperature: -10 – 70°C (14 – 158°F)
- Humidity (noncondensing): < 85%

System Requirements

- Windows 7/8.1/10
- Mac OS 10.8 or above

Package Contents

- SuperSpeed USB-C to Dual HDMI Multiport Adapter
- Quick Instruction Guide



