



USB-C to DVI Converter with Power Delivery Port

Supports up to 1920x1200@60Hz Resolution, Power Delivery (PD) up to 60 W (20 V / 3 A), Black

Part No.: [153423](#)

EAN-13: 0766623153423 | UPC: 766623153423

Our USB-C to DVI Converter with Power Delivery (PD) Port: high-resolution DVI from your device's USB-C port and power for all devices

The Manhattan USB-C to DVI Converter with PD Port makes it easy to show content from your USB-C device on an existing DVI display, monitor or projector. This converter is easy and quick to install — no settings or adjustments required. It is a compact yet powerful solution that helps avoid extra cables, tangles and clutter to keep workspaces neat and tidy.

USB-C Power Delivery

The included USB-C PD port gives up to 60 W (20 V / 3 A) to all devices in your setup. Connecting the upstream device's cable and power adapter supplies power to the upstream device and boosts the high-resolution signal for a high-quality picture. The PD function also provides faster charging than standard chargers since it finds out the power needs of compatible devices and supplies it at the quickest and safest rate.

Features:

- Supports resolutions up to 1920x1200@60Hz
- Supports Power Delivery (PD) up to 60 W (20 V / 3 A)
- Supports USB Power Delivery (PD) function up to 60 W; requires an external PD charger – available from Manhattan
- Thunderbolt 3 compatible
- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Plug and Play; requires no external power supply

- Compatible with DVI-I and DVI-D interfaces
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime warranty

Specifications:

Standards and Certifications

- USB 3.2 Gen 1
- DP 1.2 Alternate Mode
- PD 3.0
- DVI
- CE
- FCC
- RoHS2
- WEEE

Connections

- USB type C, 24-pin, male
- DVI-I, 29-pin, female
- Power Delivery USB-C port

Video Resolutions

- 1920x1200@60Hz
- 1080p
- 720p
- 1024x768
- 800x600
- 640x480

Physical

- 32-AWG cable gauge
- Mylar and aluminum shielding
- Thermal plastic casing
- Dimensions: 60 x 40 x 16 mm (2.36 x 1.57 x 0.63 in.)
- Cable length: 19.5 cm (7.67 in.)
- Weight: 36.05 g (1.27 oz.)
- Shielded
- Housing: ABS plastic

Operating Environment

- Operation Temperature: 0 – 50°C (32 – 122°F)
- Storage Temperature: -40 – 85°C (-40 – 185°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- Windows XP/Vista/7/8.1/10

- Mac 9.x/10.x or above
- Android

Package Contents

- USB-C to DVI Converter with Power Delivery Port
- Quick Instruction Guide



