



SuperSpeed USB-C Multiport Adapter

USB 3.2 Gen 1 Type-C Male to HDMI (4K@30Hz) Female, Three Top-Mounted SuperSpeed USB-A Ports, USB-C Power Delivery (PD 3.0) Port, Gigabit RJ45 Port and SD/MicroSD Card Reader; Aluminum, Black

Part No.: [152440](#)

EAN-13: 0766623152440 | UPC: 766623152440

An all-in-one USB-C Multiport Adapter for reliable connections to your devices

The Manhattan SuperSpeed USB-C Multiport Adapter makes your limited USB-C device more complete and accessible. It's a comprehensive connectivity solution that helps you do more with the devices you already have to increase productivity nearly anywhere you are. The 4K HDMI port lets you connect your current HDMI display, monitor or projector so you can expand your workspace or share what you're working on. You can add up to three peripherals, such as a mouse, keyboard, hub, external memory devices and more with its three top-mounted SuperSpeed USB-A ports. Its included SD and MicroSD slots connect you to external memory cards. Also, if you need a wired connection to a network, it offers gigabit speeds at its built-in Ethernet port.

Superior, secure connections to Ethernet, your HDMI display, USB peripherals and SD memory cards

The Manhattan SuperSpeed USB-C Multiport Adapter is easy and quick to install. This adapter enhances the functionality of your type-C device right when you connect it. There are no settings to configure or additional steps to get your devices working. Its design gives you a compact, complete solution that avoids extra cables, tangles and clutter to keep your workspace neat and tidy.

USB-C Power Delivery

The included USB-C Power Delivery port can give up to 100 W (20 V / 5 A) to all devices in your setup. You plug in the upstream device's cable and power adapter, and power flows to whatever you've connected to the Hub as well as the upstream device. The Power Delivery function also provides faster charging than standard chargers since it finds out the power needs of compatible devices and supplies it at the quickest and safest rate.

Multiport Adapter that's made to go with you

Sturdy aluminum housing makes this multiport adapter the perfect travel companion. Slip it into your computer bag with your main device, and you can always get work done using compatible devices and displays.

Features:

- Durable, portable and powerful USB-C hub that connects you to the network, your display, multiple USB devices and external memory
- One UHD 4K HDMI port, three top-mounted USB 3.2 Gen 1 type-A ports, USB-C Power Delivery (PD) port up to 100 W (20 V / 5 A), 10/100/1000 Mbps Ethernet port, and SD / MicroSD card reader
- Supports up to 4K@30Hz resolution in Mirror or Extended mode
- Up to 5 Gbps data transfer speeds on USB ports following USB 3.2 Gen 1 specification
- Gigabit speeds (10/100/1000 Mbps) on Ethernet port
- Data transfer speeds up to 800 Mbps and automatic card detection through SD and MicroSD card-reader ports
- Supports Power Delivery up to 100 W (20 V at 5 A) for all connected devices
- Supports USB Power Delivery (PD) function up to 100 W; requires an external PD charger – available from Manhattan
- Durable aluminum housing, making it the perfect desktop or travel companion
- Compatible with all USB-C DP Alt Mode devices
- Plug and play
- Maximum flexibility with 30 cm (11.8 in.) cable
- Three-year warranty

Specifications:

Standards and Certifications

- USB 3.2 Gen 1
- HDMI 1.4
- HDCP 1.4

- CE
- FCC
- RoHS2
- WEEE

General

- Video Resolutions:
 - 640 x 480
 - 800 x 600
 - 1024 x 768
 - 1920 x 1080 (1080p@60Hz)
 - 1920 x 1200
 - 3840 x 2160p at 30 Hz (4K@30Hz)
- USB-A ports: 5 Gbps
- Ethernet port: 10/100/1000 Mbps
- Supported flash cards: SD / MicroSD / SDHC / SDXC / EXTREME SD / EXTREME II SD / EXTREME III SD / ULTRA SD / ULTRA II SD / ULTRA II SD P PLUS / SD-ULTRA-X / ULTRA SPEED SD / SD PRO / SD ELITE PRO / HS SD / MMC / MMC 4.0 / HS MMC / HS RS MMC / RS MMC / RS MMC 4.0 / MMC Mobile; up to 128 GB
- Transfer speed: up to 800 Mbps
- 34-AWG cable gauge
- Bus-powered
- USB-C PD Charging Port: 100 W (20 V at 5 A)
- Mylar and aluminum shielding
- Withstanding voltage: 300 VDC
- Insulation resistance: 10 MOhm
- Conductive resistance: 5 Ohm

Connections

Input:

- One USB-C 24-pin, male

Outputs:

- One HDMI 19-pin, female
- One 10/100/1000 Mbps RJ45, female
- Three USB-A 4-pin, female
- One SD memory slot
- One MicroSD memory slot
- One USB-C 24-pin, Power Delivery, female

Physical

- Dimensions: 105 x 45 x 18 mm (4.13 x 1.77 x 0.71 in.)
- Cable Length: 30 cm (11.8 in.)
- Weight: 80 g (2.82 oz.)
- Housing: aluminum

Operating Environment

- Operation Temperature: 0 – 45°C (32 – 113°F)

- Storage Temperature: -10 – 70°C (14 – 158°F)
- Humidity (noncondensing): 10 – 90%

System Requirements

- DP Alt Mode supported devices
- Windows XP/Vista/7/8.1/10
- Linux
- Mac OS 10.7.1 or above

Package Contents

- SuperSpeed USB-C Multiport Adapter
- Quick Instruction Guide



