



GaN Tech Power Delivery Wall Charger - 65 W

Ultra-compact GaN Technology, USB-C Power Delivery (PD) Port up to 65 W, Interchangeable US, EU and UK Plugs, Black

Part No.: [102278](#)

EAN-13: 0766623102278 | UPC: 766623102278

GaN Tech Power Delivery Wall Charger - 65 W — Power up your devices with a portable, powerful charger.

Enjoy complete charging power with the Manhattan GaN Tech Power Delivery Wall Charger - 65 W. The charger's built-in gallium nitride (GaN) circuitry means you get a better charge for your devices at a smaller size than silicone provides. This charger uses Power Delivery (PD) technology to power up any device with a USB-C charging port, from laptops to mobile phones. With a foldable plug for charging in the US and swappable plugs for charging in the EU and UK, it's the perfect companion for travelers, offering a stylish, compact and ultra-modern design. It also smartly protects itself and your devices from short-circuits, over-voltage, over-current and overheating.

Features:

- GaN tech & PI chipset for maximum charging efficiency to over 93%
- USB-C Power Delivery (PD) port delivering up to 65 W to charge a notebook, laptop, Ultrabook™, tablet or other USB-C powered device
- USB-C Power Delivery (PD) port delivering up to 65 W
- Supplied with interchangeable US, EU and UK plugs
- Overload, over-current and overheat protection
- Ultra-compact, portable and stylish design for easy travel

- Three-year warranty

Specifications:

Standards and Certifications

- USB 2.0
- PD 3.0
- FCC
- ETL
- CE
- RoHS
- WEEE

General

- Gallium Nitride (GaN tech)
- AC input: 100 – 240 V; 50 – 60 Hz
- USB-C output: 5 – 20 V; maximum 3 A; 65 W
- Voltage/current settings (maximum):
 - USB-C:
 - 5 V / 3 A
 - 9 V / 3 A
 - 12 V / 3 A
 - 15 V / 3 A
 - 20 V / 3.25 A

Input Characteristics

- AC rated voltage: 100 – 240 V
- Frequency range: 50 – 60 Hz (± 1 Hz)
- Current: ? 1 A at 100 VAC 60 Hz

Output Characteristics

- Rated voltage: 5 / 9 / 12 / 15 / 19 / 20 V
- Current: 3 A maximum (at constant voltage mode)
- Rated power: 65 watts maximum
- Overshoot voltage: ? 5%

Protection Characteristics

- Short-circuit (SCP) with auto-recovery mode
- Over-voltage (OVP) with auto-recovery mode
- Over-current (OCP) — current limit: 150% (max)
- Over-temperature (OTP)

Physical

- Dimensions: 51 x 51 x 28 mm (2.01 x 2.01 x 1.1 in.)
- Weight: 0.16 kg (4.9 oz.)
- Housing: plastic

Operating Environment

- Operation Temperature: 0 – 30°C (32 – 86°F)
- Storage Temperature: -20 – 65°C (-4 – 149°F)
- Humidity (noncondensing): 10 – 90%

Package Contents

- GaN Tech Power Delivery Wall Charger - 65 W
- Interchangeable EU and UK plugs (US built-in)
- Instructions



