



Powerbank 20,000 mAh with Power Delivery & Wireless Charging Pads

Two Wireless Charging Pads (10 W & 2 W), USB-C PD Port up to 60 W, USB-A QC 3.0 Charging Port up to 24 W, White/Silver

Part No.: [102469](#)

EAN-13: 0766623102469 | UPC: 766623102469

A 20,000 mAh powerbank for notebooks and so much more

The Manhattan Powerbank 20,000 mAh with Power Delivery & Wireless Charging Pads provides all the charging power you could ask for. With an ultra-high capacity of 20,000 mAh, the powerbank offers multiple charging options so you can charge up plenty of mobile devices on the go. Charge compatible devices wirelessly on the 10-W fast-charging pad or switch to the additional 2-W charging pad to power-up an Apple Watch®. If you prefer ultra-fast wired charging, this 20,000 mAh powerbank lets you choose between the 24-W QC 3.0 USB-A port or 60-W USB-C PD port. The latter is even powerful enough to charge laptops such as the Macbook Pro® or the Microsoft® Surface®. A digital number display keeps you informed of the remaining battery level. When it runs out, you can recharge it quickly with the 45 W PD input port or, if you're an Apple® user, you can recharge it via the Lightning® port with power up to 5 V / 2 A. Should you need a light in dark corners, there's also a convenient built-in flashlight. All your valuable connected devices are safe thanks to the powerbank's protection against overload, overcurrent and overheating.

Features:

- Ultra-powerful powerbank with two wireless and two wired charging output options
- USB-C Power Delivery (PD) port delivering up to 60 W to charge a notebook, Ultrabook™, Macbook Pro®, tablet or other USB-C powered device
- Provides up to 20,000 mAh on the go when power sockets are unavailable
- Wirelessly fast-charges compatible devices - phone, cases, earbuds and more - with power up to 10 W
- Wireless charger for Apple Watch® with power up to 2 W
- USB-C PD port delivering up to 60 W
- QC 3.0 charging port delivering up to 24 W to fast-charge any compatible device
- Overload, overcurrent and overheat protection
- Digital number display to see battery status at a glance
- High-capacity, efficient lithium-polymer battery for long, reliable service
- Quick recharging via USB-C port with input up to 45 W
- Recharging via Apple Lightning® port with input up to 5 V / 2 A
- Built-in LED flashlight
- One-year warranty

Specifications:

Standards and Certifications

- CE
- FCC
- RoHS
- PD 3.0

Electrical

- Voltage/current settings (maximum):
 - USB-C PD 45-W input:
 - 5 V / 3 A
 - 9 V / 3 A
 - 12 V / 3 A
 - 15 V / 3 A
 - 20 V / 2.25 A
 - Apple Lightning® Input:
 - 5 V / 2 A
 - USB-C PD 60-W output:
 - 5 V / 3 A
 - 9 V / 3 A
 - 12 V / 3 A
 - 15 V / 3 A
 - 20 V / 3 A
 - USB-A QC 3.0 24-W output:
 - 5 V / 2.4 A
 - 3.6 - 12 V / 2 A

Battery

- Type: one lithium-polymer, built-in

- Capacity: 20,000 mAh
- Watt-hours: 72
- Digital number display of battery-charge percentage
- Button to activate LED and check battery status

Protection Characteristics

- Short-circuit (SCP) with auto-recovery mode
- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) — current limit: 150% (max)
- Over-temperature (OTP)

Compatibility - main wireless charging pad

- 10 W fast-charge mode:
 - Samsung Galaxy S7 / S7 Edge / S8 / S8+ / S9 / S9+ / S10 or above
 - Huawei Mate20 Pro, Mate20 RS, P20 Pro, P30 Pro or above
 - Samsung Note 8 / 9 / 10 or above
- 7.5 W mode:
 - Apple iPhone 8 / 8 Plus / X / XR / XS / XS Max / 11 / 11 Pro / 11 Pro Max or above
- 5 W mode:
 - All other wireless-enabled devices

Compatibility - Apple Watch® wireless charging pad

- 2 W charge mode: Apple Watch Series 1 / 2 / 3 / 4 / 5 or above

Physical

- Dimensions: 162 x 77 x 30 mm (6.38 x 3.03 x 1.18 in.)
- Weight: 475 g (16.76 oz.)

Operating Environment

- Operation temperature: 0 - 50°C (32 - 122°F)
- Storage temperature: -10 - 70°C (14 - 158°F)
- Humidity (noncondensing): 5 - 90% RH

Package Contents

- Powerbank 20,000 mAh with Power Delivery & Wireless Charging Pads
- USB-C male to USB-A male cable, 1 m (3.3 ft.)
- Quick Instruction Guide



