



## USB 3.2 Gen 1 Type-C Extension Cable

USB-C Male to USB-C Female, 1 m (3 ft.), SuperSpeed USB (Formerly USB 3.0), 5 Gbps, 60 W / 3 A, Gold-plated Contacts, Black

Part No.: [355681](#)

EAN-13: 0766623355681 | UPC: 766623355681

### USB C to USB C Extension Cable - Extend, connect and charge with 60 W and 5 Gbps

The Manhattan USB 3.2 Gen 1 USB-C Extension Cable extends port access for easier device management or adds length to a shorter cable. Sync music, photos or data with super-fast speeds up to 5 Gbps. Aluminum foil, Mylar braid double-shielding and gold-plated contacts ensure superior-quality connectivity. Its reversible USB-C plug and port will always connect to devices, no matter which way the ends of the cable are sitting.

### Power Delivery (PD) support to fast-charge even a laptop

Thanks to USB 3.2 Gen 1 versatility, you can use this cable to charge a laptop, Apple Macbook®, Macbook® Pro, Google Chromebook™, tablet and more with power up to 60 W from a USB-C wall charger, power bank or car charger (available from Manhattan).

### Features:

- USB-C male to USB-C female to extend port access for easier device management or add length to a shorter cable
- USB 3.2 Gen 1 compliant (formerly USB 3.0) with SuperSpeed transfer rates up to 5 Gbps
- Supports USB Power Delivery (PD) and Quick Charge™ (QC) up to 60 W
- Charges a USB-C powered device such as a notebook, Macbook Pro® or

tablet from a USB-C PD wall charger or powerbank

- Double shielded to reduce EMI and other interference sources
- Gold-plated contacts for corrosion-free connections
- Thunderbolt 3 compatible
- Supports current of up to 3 A
- Lifetime warranty

## Specifications:

### Standards and Certifications

- USB 3.2 Gen 1
- UL 2725
- CE
- RoHS

### General

- One USB-C 24-pin male
- One USB-C 24-pin female
- Double shielding: aluminum foil and Mylar braid
- Gold-plated contacts
- Molded PVC boot
- Thermal plastic casing
- 30/24 AWG
- Length: 1 m (3 ft.)
- Outer diameter (OD): 4.5 mm (0.18 in.)
- Weight: 30 g (1.06 oz.)

### Electrical

- Withstanding voltage: 300 VDC 10 ms
- Insulation resistance: 10 MOhm min.
- Contact resistance: 2 Ohm max.
- Supported power throughput: 60 W

### Operating Environment

- Operation temperature: 0 - 40°C (32 - 104°F)
- Storage temperature: -20 - 60°C (-4 - 140°F)
- Humidity (noncondensing): 0 - 96%

### Package Contents

- USB C to USB C Extension Cable, USB 3.2 Gen 1 (5 Gbps)

