



## **USB 3.2 Gen 1 Type-C Device Cable**

**USB-C Male to USB-C Male, 3 m (10 ft.), SuperSpeed USB (Formerly USB 3.0), 5 Gbps, 60 W / 3 A, 4K@60Hz, Black**

Part No.: [355674](#)

EAN-13: 0766623355667 | UPC: 766623355667

---

### **USB C to USB C Cable - Connect at speeds up to 5 Gbps and charge with power up to 60 W / 3 A**

The Manhattan USB 3.2 Gen 1 Type-C Device Cable easily connects a USB-C device to a USB-C port. Sync music, photos or data with super-fast speeds up to 5 Gbps. Aluminum foil, Mylar braid double-shielding and gold-plated contacts ensure superior-quality connectivity. The reversible USB-C connector will always fit, no matter which way you insert the cable.

#### **Power Delivery (PD) support to fast-charge even a laptop**

Thanks to the versatility of USB 3.2, you can use this cable to charge a laptop, Apple Macbook®, Macbook® Pro, Google Chromebook™, tablet and more with power up to 60 W from a USB-C wall charger, power bank or car charger (available from Manhattan).

#### **Features:**

- USB-C male to USB-C male for connecting a USB-C device to a USB-C port
- USB 3.2 Gen 1 compliant (formerly USB 3.0) with SuperSpeed transfer rates up to 5 Gbps
- Supports USB Power Delivery (PD) and Quick Charge™ (QC) up to 60 W
- Charges a USB-C powered device such as a notebook, Macbook Pro® or tablet from a USB-C PD wall charger or powerbank
- USB-C compliance with DisplayPort 1.2 Alternate Mode (DP Alt Mode) for resolutions up to 4K@60Hz on supported devices and displays

For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Double shielded to reduce EMI and other interference sources
- Gold-plated contacts for corrosion-free connections
- Thunderbolt 3 compatible
- Supports current up to 3 A
- Lifetime warranty

## Specifications:

### Standards and Certifications

- USB 3.2 Gen 1
- UL 2725
- CE
- RoHS

### General

- Two USB-C 24-pin males
- Double shielding: aluminum foil and Mylar braid
- Gold-plated contacts
- Molded PVC boot
- Thermal plastic casing
- 30/23 AWG
- Length: 3 m (10 ft.)
- Outer diameter (OD): 5.5 mm (0.22 in.)
- Weight: 120 g (4.23 oz.)

### Electrical

- Withstanding voltage: 300 VDC 10 ms
- Insulation resistance: 10 MOhm min.
- Contact resistance: 2 Ohm max.
- Supported power throughput: 60 W

### Operating Environment

- Operation temperature: 0 - 40°C (32 - 104°F)
- Storage temperature: -20 - 60°C (-4 - 140°F)
- Humidity (noncondensing): 0 - 96%

### Package Contents

- USB-C to USB-C Cable, USB 3.2 Gen 1 (5 Gbps)

