



Wired Optical USB Mouse

USB-A, Three Buttons with Scroll Wheel, 1000 dpi, Ambidextrous, Black/Orange

Part No.: [190091](#)

EAN-13: 0766623190091 | UPC: 766623190091

Wired Optical USB Mouse - Reliable, durable and comfortable

The Manhattan Optical USB Mouse with its 1000-dpi resolution sensor offers a reliable performance in a sturdy, practical design. Its compact size, ambidextrous shape and familiar configuration (three buttons with scroll wheel) make it ideal for daily computing needs. Plug-and-play capability with Windows[®], Mac[®] and Linux[®] compatibility makes installation quick and easy.

Features:

- Precise, accurate optical sensor with 1000 dpi
- Ambidextrous design for left- and right-handed users
- Sturdy construction for agile, reliable performance
- Low-friction base smoothly glides over work surfaces
- Plug-and-play installation; Windows[®], Mac[®] and Linux[®] compatible
- One-year warranty

Specifications:

Standards and Certifications

- USB

General

- Mouse: optical sensor; 1000 dpi resolution
- Controls: right and left mouse with scroll wheel (auto-scroll)

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Connection: USB-A
- Input voltage: 5.0 V DC / <100 mA
- Lifespan: ~ 1 million clicks

Physical

- Mouse dimensions (L x W x H): 94 x 54 x 36 mm (3.7 x 2.13 x 1.42 in.)
- Cable length: 1 m (3 ft.)
- Weight: 56 g (1.98 oz.)
- Material: HIPS plastic

Environmental

- Operation temperature: -10 - 40°C (14 - 104°F)
- Storage temperature: -15 - 60°C (5 - 140°F)
- Humidity (noncondensing): 5 - 90% RH

System Requirements

- Compatible with Windows 98/ME/2000/XP/Vista/7/8.1/10, macOS and Linux

Package Contents

- Wired Optical USB Mouse
- Quick Instruction Guide



