



USB 3.0 Type-A Active Extension Cable

USB-A Male to USB-A Female, 10 m (33 ft.), SuperSpeed USB (USB 3.2 Gen 1), 5 Gbps, Black

Part No.: [153621](#)

EAN-13: 0766623153621 | UPC: 766623153621

USB Extension Cable - Easily overcome distance limitations to connect USB devices

Use the Manhattan USB 3.0 Type-A Active Extension Cable to connect a computer USB port to a USB device almost anywhere in the room. This cable gives you an additional 10 m (33 ft.) to the existing connection without signal loss. It is fully compliant with USB 3.2 Gen 1 (formerly known as USB 3.0) specifications to help appropriate devices operate at maximum performance, and it's backward compatible with earlier versions for greater flexibility. Plug-and-play capability on Windows[®] 7/8.1/10/11 and macOS[®] systems makes the cable a great choice to link computers and peripherals in the home and office.

Features:

- Extends and boosts the signal to any USB device - supports data transfer speeds up to 5 Gbps
- Built-in repeater helps maintain USB 3.2 Gen 1 signal quality, electrical and timing specifications
- Extends the connections to enclosures and other peripherals up to 10 m (33 ft.) without signal loss
- Plug and play; Windows 7/8.1/10/11 and macOS compatible; bus powered - requires no external power supply

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Three-year warranty

Specifications:

Standards and Certifications

- USB 3.2 Gen 1
- CE
- RoHS
- FCC

Electrical

USB power output: 5.0 V \pm 5% / 0.18 A / 0.9 W

General

- Throughput: 5 Gbps
- All USB-supported operating systems
- Bus powered

Connectors

- USB 3.2 Gen 1 Standard-A male
- USB 3.2 Gen 1 Standard-A female
- Nickel plated
- Molded PVC boot

Cable

- 28 AWG conductors
- Shielded
- Withstanding voltage: 300 V DC 10 ms
- Insulation resistance: 5 MOhm
- Contact resistance: 10 Ohm
- Thermal plastic casing

Package Contents

- SuperSpeed USB Active Extension Cable

