




Cat6a 10G Toolless Keystone Jack

For Easy and Quick Snap-in Deployment, UTP, for Solid Wire, Gold-plated Contacts, Metal Housing, White

Part No.: **771962**

EAN-13: 0766623771962 | UPC: 766623771962

Cat6a UTP 10G Keystone Jack for easy, fast and tool-free deployment

The Cat6a 10G Toolless Keystone Jack from Intellinet Network Solutions is designed for quick, seamless deployment. This module easily snaps into blank patch panels, wall plates or surface connection boxes without special tools. This keystone jack is suitable for solid conductor cables in high-performance network applications up to 10GBase-T and PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE. It is equipped with gold-plated contacts for high signal integrity.

Features:

- For easy, time-saving and tool-free deployment in blank patch panels, wall plates or surface connection boxes
- Cat6a Class EA RJ45 module with 10G and 500 MHz in accordance with ISO/IEC 11801
- Gold-plated contacts for corrosion-free connections
- Supports solid wire with AWG 26/1 to 23/1
- Ideal for HDBaseT and PoE applications up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- Standard 8P8C design, compatible with all network RJ45 connections

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Compatible and color-coded with T568A and T568B
- UL approved
- Fully backward compatible with all the previous cable categories, including Category 6, 5e and 5
- Lifetime warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- ISO/IEC 11801
- UL
- REACH
- UKCA

General

- Supports transfer speeds up to 10 Gbps
- Max. operating frequency: 500 MHz
- Supports all PoE standards up to IEEE802.3bt / PoE++ / 4PPoE / Ultra PoE
- Mating cycles: ≥ 750
- Insertion force: 30N max.
- Retention strength: 7.7 kg (17 lbs.) between jack and plug

Material

- Contacts: phosphor bronze
- Contact plating: gold
- IDC: phosphor bronze
- Housing: zinc die casting, nickel-plated
- Flammability: tested and rated in accordance with UL 94 V-0

Electrical

- Insulation resistance: ≥ 500 MOhm
- Dielectric withstanding voltage: 1,000 V DC/750 V AC
- Contact resistance: ≤ 20 MOhm
- DC resistance: ≥ 0.3 Ohm
- Current rating: 1.5 A

Physical

- Dimensions (L x W x H): 38 x 16 x 23 mm (1.5 x 0.63 x 0.91 in.)
- Net weight: 8 g (0.28 oz.)
- Gross weight: 12 g (0.42 oz.)

Environmental

- Operating temperature: -10 - 60°C (14 - 140°F)
- Storage temperature: -40 - 70°C (-40 - 158°F)
- Operating humidity (non-condensing): 10 - 90% RH

Package Contents

- Cat6a 10G Toolless Keystone Jack
- Instructions

This product is part of a group; the complete list of variations follows:

- #771948 - Cat5e UTP Toolless Keystone Jack
- #771955 - Cat6 UTP Toolless Keystone Jack
- #771962 - Cat6a UTP Toolless Keystone Jack



