



USB 3.0 Type-A to Type-B Active Cable

USB-A Male to USB-B Male, 10 m, SuperSpeed USB (USB 3.2 Gen 1), 5 Gbps, Built-in Signal Booster, Black

Part No.: [394802](#)

EAN-13: 0766623394802 | UPC: 766623394802

Active USB-B Cord / Printer Cable - go beyond the length limit of standard USB cables

Standard USB 3.0 cables have a length limit of 3 m, which is as far as passive USB cables will carry the signal. The Manhattan USB 3.0 Type-A to Type-B Active Cable lets you overcome that classic limitation to connect a USB device, such as a printer, further away.

Active signal boost

This active USB 3.0 cable beats distance restrictions by incorporating bus-powered active circuitry, which can establish a 10 m connection distance to your device.

Complete USB 3.0 features

With one USB-A male connector and one USB-B male connector, this USB cord offers a long range with fast speeds up to 5 Gbps. The double shielding (aluminum foil and braid) and corrosion-resistant contacts provide maximum signal integrity.

Features:

- USB-A male to USB-B male to connect a Type-B device to a hub or computer over long distances
- Strong built-in amplifier circuitry to overcome USB distance limitations and reduce signal loss
- USB 3.2 Gen 1 (formerly USB 3.0) with SuperSpeed transfer rates up to 5 Gbps
- Great to connect USB Type-B devices like printer, scanner, external drive, and other peripherals
- Foil and braid double shielding to reduce EMI and other interference sources
- Corrosion-resistant contacts
- Plug-and-play installation; Windows[®], macOS[®], Linux[®], Chrome OS[™], and Android[™] compatible
- Suitable for extreme operating temperatures up to 85°C
- Bus powered - no external power required
- Works with standard USB 3.0 devices; backward compatible with USB 2.0 and 1.1
- UL listed
- Three-year warranty

Specifications:**Standards and Certifications**

- UL
- CE
- FCC
- RoHS
- REACH
- UKCA

General

- One USB-A 9-pin male
- One USB-B 9-pin female
- 28/24 AWG
- Double shielding: aluminum foil and braid
- Nickel-plated contacts
- Wire: copper-clad aluminum (CCA)
- Jacket OD: 5.5 mm
- Molded PVC boot
- Length: 10 m
- Net weight: 420 g
- Gross weight: 470 g

Electrical

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Withstanding voltage: 300.0 V DC 10 ms
- Insulation resistance: 5 MOhm
- Contact resistance: 2 Ohm

Operating Environment

- Operation temperature: 0 - 85°C
- Storage temperature: -20 - 85°C
- Humidity (noncondensing): 0 - 96%

Package Contents

- USB 3.0 Type-B Active Device Repeater Cable (USB A Male to B Male)

This product is part of a group; the complete list of variations follows:

- #394796 - USB 3.0 Active Device Cable, A-Male/B-Male, 5 m
- #394802 - USB 3.0 Active Device Cable, A-Male/B-Male, 10 m
- #394819 - USB 3.0 Active Device Cable, A-Male/B-Male, 15 m, optional external power supply



